DIN EN 17038-2:2022-08 (E)

Pumps - Methods of qualification and verification of the Energy Efficiency Index for rotodynamic pump units - Part 2: Testing and calculation of Energy Efficiency Index (EEI) of single pump units (includes Corrigendum :2021)

Contents

Page

European foreword 4

Introduction 5

1 Scope 6

2 Normative references 6

3 Terms and definitions 6

4 Reference flow-time profiles and reference pressure control curves 8
4.1 General 8
4.2 Reference flow-time profiles 9
4.3 Reference pressure control curves 10

5 Determination of average electric power input P1,avg by test 10
5.1 General 10
5.1.1 Test requirements 10
5.1.2 Test conditions 10
5.1.3 Measuring instrumentation 11
5.2 Calculation of load points 12
5.2.1 General 12
5.2.2 Determination of Q100 % and H100 % 12
5.2.3 ~Determination of part load and over load points and reference control curveTM 13
5.3 Calculation of P1,avg 14
5.3.1 General 14
5.3.2 Pump units evaluated with the reference flow-time profile for constant flow operation 14
5.3.3 Pump units evaluated with the reference flow-time profile for variable flow operation 14
5.3.4 Procedures for testing and evaluation of pump units with special pump types 15

6 Determination of the Energy Efficiency Index of pump units by the means of a semi-analytical model 16
6.1 General 16
6.2 The semi analytical model of the pump 17
6.3 Pump units in fixed speed operation 19
6.3.1 General 19
6.3.2 The model of the electric motor 20
6.3.3 Interaction of pump and motor 21
6.3.4 Determination of Q100 % from QBEP 22
6.3.5 Determination of the P1,avg,c-value 23
6.4 Pump units with a Power Drive System (PDS) 24
6.4.1 General 24
6.4.2 The model of the Power Drive System (PDS) 26
6.4.3 Interaction between pump and PDS 29
6.4.4 Determination of Q100 % and H100 % from QBEP and HBEP 30
6.4.5 Determination of P1,avg,v and P1,avg,c for pump units with PDS 31

7 Determination of reference electric power input P1,ref 32

8 Calculation of Energy Efficiency index (EEI) 35

Annex A (normative) Scope 36

Annex B (informative) Determination of additional supporting points for semi-analytical model based on empirical correlations 39

B.1 General 39
B.2 Additional supporting points for end-suction pumps (pump types ESOB, ESCC and ESCCi) 41
B.2.1 Additional supporting points at Q/QBEP = 0,25 41
B.2.2 Additional supporting points at Q/QBEP = 0,1 41
B.3 Additional supporting points for vertical multistage pump (MS-V) 42
B.3.1 Additional supporting points at Q/QBEP = 0,25 42
B.3.2 Additional supporting points at Q/QBEP = 0,1 42
B.4 Maximum model uncertainties 42

Annex C (normative) Synthesis of the PDS supporting points from separate data for motor and CDM 46

C.1 General 46
C.2 Determination of the losses PL,CDM at the 3-supporting points needed for the PDS model 49
C.3 Determination of the losses PL,PDS at the 3 supporting points needed for the PDS model 50

Annex D (informative) Uncertainties and tolerances of EEI-values 52

D.1 General remarks 52
D.2 The measurement uncertainty of the EEI-value determined by test 52
D.3 The uncertainty of the EEI-value determined by the application of models 55
D.3.1 General 55
D.3.2 Operation mode: Fixed speed 55
D.3.3 Operation mode: Variable speed 56
D.4 The total tolerance of the mean EEI-value 58
D.4.1 Determination of the mean EEI-value by testing only one pump unit 58
D.4.2 Determination of the mean EEI-value by testing a sample of M pump units of the same type series 60
D.4.3 Determination of the mean EEI-value by application of the semi-analytical model 60

Annex E (informative) Mathematical solution of polynomial formulae of 3rd degree 63

Annex F (normative) CDM model fall back values for Semi Analytical Model 65

Bibliography 66