

# DIN EN 17038-2:2022-08 (E)

## Pumps - Methods of qualification and verification of the Energy Efficiency Index for rotodynamic pump units - Part 2: Testing and calculation of Energy Efficiency Index (EEI) of single pump units (includes Corrigendum :2021)

---

<b>Contents</b>		<b>Page</b>
European foreword .....		4
Introduction .....		5
<b>1</b>	<b>Scope .....</b>	<b>6</b>
<b>2</b>	<b>Normative references .....</b>	<b>6</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>6</b>
<b>4</b>	<b>Reference flow-time profiles and reference pressure control curves .....</b>	<b>8</b>
4.1	General .....	8
4.2	Reference flow-time profiles .....	9
4.3	Reference pressure control curves .....	10
<b>5</b>	<b>Determination of average electric power input P<sub>1,avg</sub> by test .....</b>	<b>10</b>
5.1	General .....	10
5.1.1	Test requirements .....	10
5.1.2	Test conditions .....	10
5.1.3	Measuring instrumentation .....	11
5.2	Calculation of load points .....	12
5.2.1	General .....	12
5.2.2	Determination of Q <sub>100</sub> % and H <sub>100</sub> % .....	12
5.2.3	~Determination of part load and over load points and reference control curve <sup>TM</sup> .....	13
5.3	Calculation of P <sub>1,avg</sub> .....	14
5.3.1	General .....	14
5.3.2	Pump units evaluated with the reference flow-time profile for constant flow operation .....	14
5.3.3	Pump units evaluated with the reference flow-time profile for variable flow operation .....	14
5.3.4	Procedures for testing and evaluation of pump units with special pump types .....	15
<b>6</b>	<b>Determination of the Energy Efficiency Index of pump units by the means of a semi-analytical model .....</b>	<b>16</b>
6.1	General .....	16
6.2	The semi analytical model of the pump .....	17
6.3	Pump units in fixed speed operation .....	19
6.3.1	General .....	19
6.3.2	The model of the electric motor .....	20
6.3.3	Interaction of pump and motor .....	21
6.3.4	Determination of Q <sub>100</sub> % from QBEP .....	22
6.3.5	Determination of the P <sub>1,avg,c</sub> -value .....	23
6.4	Pump units with a Power Drive System (PDS) .....	24
6.4.1	General .....	24
6.4.2	The model of the Power Drive System (PDS) .....	26
6.4.3	Interaction between pump and PDS .....	29
6.4.4	Determination of Q <sub>100</sub> % and H <sub>100</sub> % from QBEP and HBEP .....	30
6.4.5	Determination of P <sub>1,avg,v</sub> and P <sub>1,avg,c</sub> for pump units with PDS .....	31
<b>7</b>	<b>Determination of reference electric power input P<sub>1,ref</sub> .....</b>	<b>32</b>

<b>8</b>	<b>Calculation of Energy Efficiency index (EEI)</b> .....	<b>35</b>
	<b>Annex A (normative) Scope</b> .....	<b>36</b>
	<b>Annex B (informative) Determination of additional supporting points for semi-analytical model based on empirical correlations</b> .....	<b>39</b>
<b>B.1</b>	<b>General</b> .....	<b>39</b>
<b>B.2</b>	<b>Additional supporting points for end-suction pumps (pump types ESOB, ESCC and ESCCi)</b> .....	<b>41</b>
<b>B.2.1</b>	<b>Additional supporting points at Q/QBEP = 0,25</b> .....	<b>41</b>
<b>B.2.2</b>	<b>Additional supporting points at Q/QBEP = 0,1</b> .....	<b>41</b>
<b>B.3</b>	<b>Additional supporting points for vertical multistage pump (MS-V)</b> .....	<b>42</b>
<b>B.3.1</b>	<b>Additional supporting points at Q/QBEP = 0,25</b> .....	<b>42</b>
<b>B.3.2</b>	<b>Additional supporting points at Q/QBEP = 0,1</b> .....	<b>42</b>
<b>B.4</b>	<b>Maximum model uncertainties</b> .....	<b>42</b>
	<b>Annex C (normative) Synthesis of the PDS supporting points from separate data for motor and CDM</b> .....	<b>46</b>
<b>C.1</b>	<b>General</b> .....	<b>46</b>
<b>C.2</b>	<b>Determination of the losses PL,CDM at the 3-supporting points needed for the PDS model</b> .....	<b>49</b>
<b>C.3</b>	<b>Determination of the losses PL,PDS at the 3 supporting points needed for the PDS model</b> .....	<b>50</b>
	<b>Annex D (informative) Uncertainties and tolerances of EEI-values</b> .....	<b>52</b>
<b>D.1</b>	<b>General remarks</b> .....	<b>52</b>
<b>D.2</b>	<b>The measurement uncertainty of the EEI-value determined by test</b> .....	<b>52</b>
<b>D.3</b>	<b>The uncertainty of the EEI-value determined by the application of models</b> .....	<b>55</b>
<b>D.3.1</b>	<b>General</b> .....	<b>55</b>
<b>D.3.2</b>	<b>Operation mode: Fixed speed</b> .....	<b>55</b>
<b>D.3.3</b>	<b>Operation mode: Variable speed</b> .....	<b>56</b>
<b>D.4</b>	<b>The total tolerance of the mean EEI-value</b> .....	<b>58</b>
<b>D.4.1</b>	<b>Determination of the mean EEI-value by testing only one pump unit</b> .....	<b>58</b>
<b>D.4.2</b>	<b>Determination of the mean EEI-value by testing a sample of M pump units of the same type series</b> .....	<b>60</b>
<b>D.4.3</b>	<b>Determination of the mean EEI-value by application of the semi-analytical model</b> .....	<b>60</b>
	<b>Annex E (informative) Mathematical solution of polynomial formulae of 3rd degree</b> .....	<b>63</b>
	<b>Annex F (normative) CDM model fall back values for Semi Analytical Model</b> .....	<b>65</b>
	<b>Bibliography</b> .....	<b>66</b>