DIN EN ISO 16122-4:2018-09 (E)

Agricultural and forestry machines - Inspection of sprayers in use - Part 4: Fixed and semi-mobile spr ayers (ISO 16122-4:2015)

Contents

Page

Foreword **4**

Introduction **5**

1 Scope **6**

2 Normative references **6**

3 Terms and definitions **6**

4 Requirements and method of verification **7**

4.1 Leaks and dripping 7

4.1.1 Static leaks 7

4.1.2 Dynamic leaks 7

4.1.3 Spraying and dripping on parts 7

4.2 Pump(s) 7

4.2.1 Capacity 7

4.2.2 Pulsations 8

4.2.3 Air chamber 8

4.3 Spray mix agitation 8

4.3.1 Hydraulic 8

4.3.2 Mechanical 8

4.4 Spray liquid tank(s) 9

4.4.1 Lid 9

4.4.2 Filling hole(s) 9

4.4.3 Induction hopper 9

4.4.4 Pressure compensation 9

4.4.5 Tank content indicator(s) 9

4.4.6 Tank emptying 9

4.4.7 Tank filling 9

4.4.8 Cleaning device for plant protection product containers 10

4.4.9 Cleaning equipment 10

4.5 Measuring systems, controls and regulation systems 10

4.5.1 General 10

4.5.2 Pressure indicator 10

4.5.3 Other measuring devices 11

4.5.4 Pressure adjusting devices 11

4.5.5 Direct injection systems 11

4.6 Lines (pipes and hoses) 11

4.7 Filters 12

4.7.1 Filter presence 12

4.7.2 Isolating device 12

4.7.3 Filter insert changeability 12

4.8 Application unit 12

4.8.1 Dripping 12

4.8.2 Horizontal spray boom 12

4.8.3 Vertical spray boom 14

4.8.4 Spray guns and lances 15

4.9 Blower 15

4.9.1 Switching off 15

4.9.2 Adjustability 15

4.10 Distribution 15
4.10.1 Uniformity of spray jet 15
4.10.2 Nozzle output 15
4.10.3 Spray distribution measurement on a patternator (optional) 16
4.10.4 Optional vertical distribution information 16
4.11 Autonomous application units 16
4.11.1 Drive system 16
4.11.2 Travel speed spray robots 16
4.12 Cleaning equipment 17
5 Test methods 17
5.1 Test facilities 17
5.2 Spray and agitation pump(s) 17
5.2.1 Pump capacity test 17
5.2.2 Pump pulsations 19
5.3 Sprayer pressure indicators 19
5.3.1 Specifications of pressure indicators used for verification 19
5.3.2 Verification method of the sprayer pressure indicator 20
5.4 Flow meters for controlling the volume/hectare rate 20
5.4.1 General 20
5.4.2 Operating procedure No.1: Verification by nozzle flow rate measurement 20
5.4.3 Operating procedure No.2: Verification by installing a standard flow meter on the circuit of the sprayer 20
5.5 System for controlling forward speed 20
5.6 Uniformity of the transverse volume distribution with a horizontal patternator 20
5.6.1 Specification of horizontal patternators used for verification 20
5.6.2 Calculation of the coefficient of variation (CV) 21
5.6.3 Verification method of the uniformity of the transverse distribution 21
5.7 Flow rate of the spray nozzles 22
5.7.1 General 22
5.7.2 Measurement with nozzles fitted on the sprayer 22
5.7.3 Measurement with nozzles removed from the sprayer 22
5.8 Pressure drop 22
5.9 Pressure variation when the sections are closed 22
5.10 Pressure variation when the spray is switched off 22
5.11 Accuracy of direct injection systems 23
5.12 Pressure distribution 23
Bibliography 24