

# DIN EN 16842-3:2019-06 (E)

## Powered industrial trucks - Visibility - Test methods and verification - Part 3: Reach trucks up to and including 10000 kg capacity

---

<b>Contents</b>		<b>Page</b>
European foreword .....		3
Introduction .....		4
<b>1</b>	<b>Scope .....</b>	<b>5</b>
<b>2</b>	<b>Normative references .....</b>	<b>5</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>5</b>
<b>4</b>	<b>Truck configuration .....</b>	<b>6</b>
<b>4.1</b>	<b>General .....</b>	<b>6</b>
<b>4.2</b>	<b>Fork arm dimensions .....</b>	<b>6</b>
<b>5</b>	<b>Test equipment .....</b>	<b>6</b>
<b>6</b>	<b>Test procedures for direct visibility .....</b>	<b>6</b>
<b>6.1</b>	<b>Lighting equipment position .....</b>	<b>6</b>
<b>6.1.1</b>	<b>General .....</b>	<b>6</b>
<b>6.1.2</b>	<b>Stand-on operated trucks .....</b>	<b>6</b>
<b>6.1.3</b>	<b>Sit-on operated trucks .....</b>	<b>8</b>
<b>6.2</b>	<b>Test paths for reach trucks 10 000 kg .....</b>	<b>8</b>
<b>6.3</b>	<b>Measurement procedure .....</b>	<b>10</b>
<b>6.4</b>	<b>Test procedure for indirect visibility .....</b>	<b>10</b>
<b>7</b>	<b>Acceptance criteria .....</b>	<b>10</b>
<b>7.1</b>	<b>General .....</b>	<b>10</b>
<b>7.2</b>	<b>Direct visibility .....</b>	<b>10</b>
<b>7.2.1</b>	<b>General .....</b>	<b>10</b>
<b>7.2.2</b>	<b>Travelling visibility .....</b>	<b>10</b>
<b>7.2.3</b>	<b>Manoeuvring visibility .....</b>	<b>10</b>
<b>7.2.4</b>	<b>Fork arms .....</b>	<b>10</b>
<b>7.3</b>	<b>Indirect visibility .....</b>	<b>10</b>
<b>7.4</b>	<b>Criteria for reach trucks up to and including 10 000 kg rated capacity .....</b>	<b>11</b>
<b>8</b>	<b>Test report .....</b>	<b>12</b>
<b>9</b>	<b>Information for use .....</b>	<b>12</b>