ISO/TS 6336-22:2018 (E)

Calculation of load capacity of spur and helical gears — Part 22: Calculation of micropitting load capacity

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms, definitions, symbols and units

3.1 Terms and definitions
3.2 Symbols and units

4 Micropitting

5 Basic formulae

5.1 General
5.2 Safety factor against micropitting, Sλ
5.3 Local specific lubricant film thickness, λGF,Y
5.4 Permissible specific lubricant film thickness, λGFP
5.5 Recommendation for the minimum safety factor against micropitting, Sλ,min

6 Material parameter, GM

6.1 General
6.2 Reduced modulus of elasticity, Er
6.3 Pressure viscocity coefficient at bulk temperature, αθM

7 Local velocity parameter, UY

7.1 General
7.2 Sum of tangential velocities, vΣ,Y
7.3 Dynamic viscosity at bulk temperature, ηθM
7.3.1 General
7.3.2 Kinematic viscosity at bulk temperature, vθM
7.3.3 Density of the lubricant at bulk temperature, ρθM

8 Local load parameter, WY

8.1 General
8.2 Local Hertzian contact stress, pdyn,Y,A, according to Method A
8.3 Local Hertzian contact stress, pdyn,Y,B, according to Method B
8.3.1 General
8.3.2 Local nominal Hertzian contact stress, pH,Y,B

9 Local sliding parameter, SGF,Y

9.1 General
9.2 Pressure viscosity coefficient at local contact temperature, αθB,Y
9.3 Dynamic viscosity at local contact temperature, ηθB,Y
9.3.1 General
9.3.2 Kinematic viscosity at local contact temperature, vθB,Y
9.3.3 Density of the lubricant at local contact temperature, ρθB,Y

10 Definition of contact point Y on the path of contact

11 Load sharing factor, XY

11.1 General

11.2 Spur gears with unmodified profiles
11.3 Spur gears with profile modification
11.4 Local buttressing factor, Xbut,Y
11.5 Helical gears with εβ ≤ 0,8 and unmodified profiles
11.6 Helical gears with εβ ≤ 0,8 and profile modification
11.7 Helical gears with εβ ≥ 1,2 and unmodified profiles
11.8 Helical gears with εβ ≥ 1,2 and profile modification
11.9 Helical gears with 0,8 < εβ < 1,2

12 Local contact temperature, θB,Y

13 Local flash temperature, θfl,Y

14 Bulk temperature, θM

14.1 General
14.2 Mean coefficient of friction, μm
14.3 Load losses factor, Hv
14.4 Tip relief factor, XCa
14.5 Lubricant factor, XS

Annex A (informative) Calculation of the permissible specific lubricant film thickness for oils with a micropitting test result according to FVA-Information Sheet 54/7

Annex B (informative) Guideline for reference values of λGFP

Page count: 38