

# ISO 6150:2018 (E)

## **Pneumatic fluid power — Cylindrical quick-action couplings for maximum working pressures of 1 MPa, 1,6 MPa, and 2,5 MPa (10 bar, 16 bar and 25 bar) — Plug connecting dimensions, specifications, application guidelines and testing**

---

### **Contents**

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Dimensions and tolerances
5	Designation
6	Requirements
6.1	Material
6.2	Hardness
6.3	Surface finish
6.4	Corrosion protection
6.5	Number of couplings and uncouplings
6.6	Test pressures
6.7	Tests at extreme working temperatures
6.8	Limited rotation for self-alignment
6.9	Structural rigidity
6.10	Leakage
7	Application guidelines
7.1	Installation with vibrating tools
7.2	Coupling and uncoupling safety considerations
8	Testing
8.1	Accuracy of test equipment and instrumentation
8.2	Checking of compliance
8.3	Hydraulic test
8.4	Corrosion test
8.5	Test for structural rigidity
8.6	Operational tests
8.6.1	Disconnect force
8.6.2	Connect force
8.6.3	Measurement of leakage at maximum working pressure
8.6.3.1	Uncoupled
8.6.3.2	Coupled
8.6.4	Extreme temperature test at maximum working pressure
8.6.4.1	Maximum operating temperature, uncoupled
8.6.4.2	Maximum operating temperature, coupled
8.6.4.3	Minimum operating temperature, uncoupled
8.6.4.4	Minimum operating temperature, coupled
9	Identification statement (Reference to this document)