

ISO 21360-3:2019 (E)

Vacuum technology — Standard methods for measuring vacuum pump performance — Part 3: Specific parameters for mechanical booster vacuum pumps

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols
5	Measurement conditions
6	Experimental setup
6.1	General
6.2	Schematic diagram
6.3	Test dome on test pump
6.4	Buffer volume on backing line
6.5	Vacuum gauges
7	Test methods
7.1	Measurement of maximum tolerable pressure difference, Δp_{\max}
7.1.1	General
7.1.2	Measuring method
7.1.3	Measuring procedure
7.1.4	Measurement uncertainty
7.1.5	Evaluation of the measurement
7.1.6	Test report
7.2	Measurement report of compression ratio K_0
7.2.1	General
7.2.2	Test report
7.3	Measurement of the effective compression ratio K_{eff}
7.3.1	Backing pump selection
7.3.2	Test report
7.4	Measurement of overflow valve pressure difference Δp_1
7.4.1	General
7.4.2	Determination of overflow valve pressure difference
7.4.3	Measuring method
7.4.4	Measuring procedure
7.4.5	Overflow valve opening
7.4.6	Measurement uncertainty
7.4.7	Evaluation of the measurement
7.4.8	Test report
8	Test report
8.1	Content
8.2	Report on pump parameters
8.3	Report on test equipment and conditions
8.4	Report on operational parameters
Annex A	(normative) Test dome

Annex B (informative) Backing line and returning cooled-gas line

Annex C (informative) Measuring uncertainties

- C.1 General remarks**
- C.2 Uncertainty of the maximum tolerable pressure difference**
- C.3 Uncertainty of the compression ratio with zero throughput**
- C.4 Uncertainty of the overflow valve pressure difference**

Page count: 14