

ISO 21360-3:2019 (E)

Vacuum technology — Standard methods for measuring vacuum pump performance — Part 3: Specific parameters for mechanical booster vacuum pumps

Contents

| | |
|---------|--|
| | Foreword |
| | Introduction |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Symbols |
| 5 | Measurement conditions |
| 6 | Experimental setup |
| 6.1 | General |
| 6.2 | Schematic diagram |
| 6.3 | Test dome on test pump |
| 6.4 | Buffer volume on backing line |
| 6.5 | Vacuum gauges |
| 7 | Test methods |
| 7.1 | Measurement of maximum tolerable pressure difference, Δp_{max} |
| 7.1.1 | General |
| 7.1.2 | Measuring method |
| 7.1.3 | Measuring procedure |
| 7.1.4 | Measurement uncertainty |
| 7.1.5 | Evaluation of the measurement |
| 7.1.6 | Test report |
| 7.2 | Measurement report of compression ratio K_0 |
| 7.2.1 | General |
| 7.2.2 | Test report |
| 7.3 | Measurement of the effective compression ratio K_{eff} |
| 7.3.1 | Backing pump selection |
| 7.3.2 | Test report |
| 7.4 | Measurement of overflow valve pressure difference Δp_1 |
| 7.4.1 | General |
| 7.4.2 | Determination of overflow valve pressure difference |
| 7.4.3 | Measuring method |
| 7.4.4 | Measuring procedure |
| 7.4.5 | Overflow valve opening |
| 7.4.6 | Measurement uncertainty |
| 7.4.7 | Evaluation of the measurement |
| 7.4.8 | Test report |
| 8 | Test report |
| 8.1 | Content |
| 8.2 | Report on pump parameters |
| 8.3 | Report on test equipment and conditions |
| 8.4 | Report on operational parameters |
| Annex A | (normative) Test dome |

Annex B (informative) Backing line and returning cooled-gas line

Annex C (informative) Measuring uncertainties

- C.1 General remarks**
- C.2 Uncertainty of the maximum tolerable pressure difference**
- C.3 Uncertainty of the compression ratio with zero throughput**
- C.4 Uncertainty of the overflow valve pressure difference**

Page count: 14