

# ISO 8100-1:2019 (E)

## Lifts for the transport of persons and goods — Part 1: Passenger and goods passenger lifts

---

### Contents

|           |   |
|-----------|---|
|           | Foreword  |
|           | Introduction  |
| 1         | Scope   |
| 2         | Normative references  |
| 3         | Terms and definitions   |
| 4         | List of significant hazards   |
| 5         | Safety requirements and/or protective measures                                |
| 5.1       | General   |
| 5.2       | Well, machinery spaces and pulley rooms                                       |
| 5.2.1     | General provisions  |
| 5.2.1.1   | Arrangement of lift equipment   |
| 5.2.1.2   | Exclusive use of the well, machine and pulley rooms                           |
| 5.2.1.3   | Ventilation of the well, machinery spaces and pulley rooms                    |
| 5.2.1.4   | Lighting  |
| 5.2.1.5   | Electric equipment in the pit and in machinery spaces and pulley rooms        |
| 5.2.1.6   | Emergency release   |
| 5.2.1.7   | Handling of equipment   |
| 5.2.1.8   | Strength of walls, floors and ceilings  |
| 5.2.1.9   | Surfaces of walls, floors and ceilings  |
| 5.2.2     | Access to well and to machinery spaces and pulley rooms                       |
| 5.2.3     | Access and emergency doors — Access trap doors — Inspection doors             |
| 5.2.4     | Notices   |
| 5.2.5     | Well  |
| 5.2.5.1   | General provisions  |
| 5.2.5.2   | Well enclosure  |
| 5.2.5.2.1 | General   |
| 5.2.5.2.2 | Totally enclosed well   |
| 5.2.5.2.3 | Partially enclosed well   |
| 5.2.5.3   | Construction of the walls of the well and landing doors facing a car entrance |
| 5.2.5.4   | Protection of any spaces located below the well                               |
| 5.2.5.5   | Protection in the well  |
| 5.2.5.6   | Guided travel of car, counterweight and balancing weight                      |
| 5.2.5.6.1 | Extreme position of car, counterweight and balancing weight                   |
| 5.2.5.6.2 | In the case of traction lifts   |
| 5.2.5.6.3 | In the case of positive drive lifts   |
| 5.2.5.6.4 | In the case of hydraulic lifts  |
| 5.2.5.7   | Refuge spaces on car roof and clearances in headroom                          |
| 5.2.5.8   | Refuge spaces and clearances in the pit                                       |
| 5.2.6     | Machinery spaces and pulley rooms   |
| 5.2.6.1   | General provisions  |
| 5.2.6.2   | Notices and instructions  |
| 5.2.6.3   | Machinery in a machine room   |
| 5.2.6.3.1 | Traction sheave in the well   |
| 5.2.6.3.2 | Dimensions  |
| 5.2.6.3.3 | Other openings  |
| 5.2.6.4   | Machinery inside the well   |
| 5.2.6.4.1 | General provisions  |

- 5.2.6.4.2 Dimensions of working areas inside the well
- 5.2.6.4.3 Working areas in the car or on the car roof
- 5.2.6.4.4 Working areas in the pit
- 5.2.6.4.5 Working areas on a platform
- 5.2.6.4.6 Working areas outside of the well
- 5.2.6.5 Machinery outside of the well
- 5.2.6.5.1 Machinery cabinet
- 5.2.6.5.2 Working area
- 5.2.6.6 Devices for emergency and test operations
- 5.2.6.7 Construction and equipment of pulley rooms
- 5.2.6.7.1 Dimensions
- 5.2.6.7.2 Openings
- 5.3 Landing doors and car doors
- 5.3.1 General provisions
- 5.3.2 Height and width of entrances
- 5.3.2.1 Height
- 5.3.2.2 Width
- 5.3.3 Sills, guides, door suspension
- 5.3.3.1 Sills
- 5.3.3.2 Guides
- 5.3.3.3 Suspension of vertically sliding doors
- 5.3.4 Horizontal door clearances
- 5.3.5 Strength of landings and car doors
- 5.3.5.1 General
- 5.3.5.2 Behaviour under fire conditions
- 5.3.5.3 Mechanical strength
- 5.3.6 Protection in relation to door operation
- 5.3.6.1 General
- 5.3.6.2 Power-operated doors
- 5.3.6.2.1 General
- 5.3.6.2.2 Horizontally sliding doors
- 5.3.6.2.2.1 Automatic power-operated doors
- 5.3.6.2.2.2 Non-automatic power-operated doors
- 5.3.6.2.2.3 Vertically sliding doors
- 5.3.6.2.3 Other types of doors
- 5.3.6.3 Reversal of closing movement
- 5.3.7 Local landing lighting and "car here" signal lights
- 5.3.7.1 Local landing lighting
- 5.3.7.2 "Car here" indication
- 5.3.8 Locking and closed landing door check
- 5.3.8.1 Protection against the risk of falling
- 5.3.8.2 Protection against shearing
- 5.3.9 Locking and emergency unlocking of landing and car doors
- 5.3.9.1 Landing door locking devices
- 5.3.9.1.1 General
- 5.3.9.2 Car door locking devices
- 5.3.9.3 Emergency unlocking
- 5.3.9.4 Electric safety device for proving the landing door closed
- 5.3.10 Requirements common to devices for proving the locked condition and the closed condition of the landing door
- 5.3.11 Sliding landing doors with multiple, mechanically linked panels
- 5.3.12 Closing of automatically operated landing doors
- 5.3.13 Electric safety device for proving the car doors closed
- 5.3.14 Sliding or folding car doors with multiple, mechanically linked panels
- 5.3.15 Opening the car door
- 5.4 Car, counterweight and balancing weight
- 5.4.1 Height of car
- 5.4.2 Available car area, rated load, number of passengers
- 5.4.2.1 General case
- 5.4.2.1.1 General
- 5.4.2.2 Goods passenger lifts
- 5.4.2.3 Number of passengers
- 5.4.3 Walls, floor and roof of the car
- 5.4.4 Car door, floor, wall, ceiling and decorative materials

- 5.4.5 Apron
- 5.4.6 Emergency trap doors and emergency doors
- 5.4.7 Car roof
- 5.4.8 Equipment on top of the car
- 5.4.9 Ventilation
- 5.4.10 Lighting
- 5.4.11 Counterweight and balancing weight
  - 5.4.11.1 General
- 5.5 Suspension means, compensation means and related protection means
  - 5.5.1 Suspension means
  - 5.5.2 Sheave, pulley, drum and rope diameter ratios, rope/chain terminations
  - 5.5.3 Rope traction
  - 5.5.4 Winding up of ropes for positive drive lifts
  - 5.5.5 Distribution of load between the ropes or the chains
  - 5.5.6 Compensation means
  - 5.5.7 Protection for sheaves, pulleys and sprockets
  - 5.5.8 Traction sheaves, pulleys and sprockets in the well
- 5.6 Precautions against free fall, excessive speed, unintended car movement and creeping of the car
  - 5.6.1 General provisions
  - 5.6.2 Safety gear and its tripping means
    - 5.6.2.1 Safety gear
      - 5.6.2.1.1 General provisions
      - 5.6.2.1.2 Conditions of use for different types of safety gear
      - 5.6.2.1.3 Retardation
      - 5.6.2.1.4 Release
      - 5.6.2.1.5 Electrical checking
      - 5.6.2.1.6 Constructional conditions
    - 5.6.2.2 Means of tripping the safety gear
      - 5.6.2.2.1 Tripping by overspeed governor
      - 5.6.2.2.2 Tripping by breakage of suspension means
      - 5.6.2.2.3 Tripping by safety rope
      - 5.6.2.2.4 Tripping by downward movement of the car
        - 5.6.2.2.4.1 Tripping by rope
        - 5.6.2.2.4.2 Tripping by lever
  - 5.6.3 Rupture valve
  - 5.6.4 Restrictors
  - 5.6.5 Pawl device
  - 5.6.6 Ascending car overspeed protection means
- 5.6.7 Protection against unintended car movement
- 5.7 Guide rails
  - 5.7.1 Guiding of the car, counterweight or balancing weight
  - 5.7.2 Permissible stresses and deflections
    - 5.7.2.1 General provisions
    - 5.7.2.2 Load cases
    - 5.7.2.3 Forces on guide rails
  - 5.7.3 Combination of loads and forces
  - 5.7.4 Impact factors
    - 5.7.4.1 Safety device operation
    - 5.7.4.2 Normal operation
    - 5.7.4.3 Auxiliary parts fixed to the guide rail and/or other operational scenarios
    - 5.7.4.4 Values of impact factors
    - 5.7.4.5 Permissible stresses
    - 5.7.4.6 Permissible deflections
    - 5.7.4.7 Calculation
- 5.8 Buffers
  - 5.8.1 Car and counterweight buffers
  - 5.8.2 Stroke of car and counterweight buffers
    - 5.8.2.1 Energy accumulation type buffers
      - 5.8.2.1.1 Buffers with linear characteristics
      - 5.8.2.1.2 Buffers with non-linear characteristics
    - 5.8.2.2 Energy dissipation type buffers
- 5.9 Lift machinery and associated equipment
  - 5.9.1 General provision

- 5.9.2 Lift machine for traction lifts and positive drive lifts
  - 5.9.2.1 General provisions
  - 5.9.2.2 Braking system
    - 5.9.2.2.1 General provisions
    - 5.9.2.2.2 Electro-mechanical brake
  - 5.9.2.3 Emergency operation
  - 5.9.2.4 Speed
  - 5.9.2.5 Removing the power which can cause rotation of the motor
    - 5.9.2.5.1 General
    - 5.9.2.5.2 Motors supplied directly from A.C. or D.C. mains by contactors
    - 5.9.2.5.3 Drive using a “Ward-Leonard” system
      - 5.9.2.5.3.1 Excitation of the generator supplied by classical elements
      - 5.9.2.5.3.2 Excitation of the generator supplied and controlled by static elements
    - 5.9.2.5.4 A.C. or D.C. motor supplied and controlled by static elements
  - 5.9.2.6 Control devices and monitoring devices
  - 5.9.2.7 Motor run time limiter
- 5.9.3 Lift machine for hydraulic lifts
  - 5.9.3.1 General provision
  - 5.9.3.2 Jack
    - 5.9.3.2.1 Calculations of cylinder and ram
      - 5.9.3.2.1.1 Pressure calculations
      - 5.9.3.2.1.2 Buckling calculations
      - 5.9.3.2.1.3 Tensile stress calculations
    - 5.9.3.2.2 Connection car/ram (cylinder)
    - 5.9.3.2.3 Limitation of the ram stroke
    - 5.9.3.2.4 Cushioned stop
    - 5.9.3.2.5 Means of protection
    - 5.9.3.2.6 Telescopic jacks
  - 5.9.3.3 Piping
    - 5.9.3.3.1 General
    - 5.9.3.3.2 Rigid pipes
    - 5.9.3.3.3 Flexible hoses
  - 5.9.3.4 Stopping the machine and checking its stopped condition
    - 5.9.3.4.1 General
    - 5.9.3.4.2 Upwards motion
    - 5.9.3.4.3 Downwards motion
    - 5.9.3.4.4 Checking of the stopped condition
  - 5.9.3.5 Hydraulic control and safety devices
    - 5.9.3.5.1 Shut-off valve
    - 5.9.3.5.2 Non-return valve
    - 5.9.3.5.3 Pressure relief valve
    - 5.9.3.5.4 Direction valves
      - 5.9.3.5.4.1 Down direction valves
      - 5.9.3.5.4.2 Up direction valves
    - 5.9.3.5.5 Filters
  - 5.9.3.6 Checking the pressure
  - 5.9.3.7 Tank
  - 5.9.3.8 Speed
  - 5.9.3.9 Emergency operation
    - 5.9.3.9.1 Moving the car downwards
    - 5.9.3.9.2 Moving the car upwards
    - 5.9.3.9.3 Checking of the car position
  - 5.9.3.10 Motor run time limiter
  - 5.9.3.11 Protection against overheating of the hydraulic fluid
- 5.10 Electric installations and appliances
  - 5.10.1 General provisions
    - 5.10.1.1 Limits of application
    - 5.10.1.2 Protection against electric shock
      - 5.10.1.2.1 General
      - 5.10.1.2.2 Basic protection (protection against direct contact)
      - 5.10.1.2.3 Additional protection
      - 5.10.1.2.4 Protection against residual voltages
    - 5.10.1.3 Insulation resistance of the electrical installation (IEC 60364-6)
  - 5.10.2 Incoming supply conductor terminations

- 5.10.3 Contactors, contactor relays, components of safety circuits
  - 5.10.3.1 Contactors and contactor relays
  - 5.10.3.2 Components of safety circuits
- 5.10.4 Protection of electrical equipment
- 5.10.5 Main switches
- 5.10.6 Electric wiring
  - 5.10.6.1 Conductors and cables
  - 5.10.6.2 Cross-sectional area of conductors
  - 5.10.6.3 Wiring practices
    - 5.10.6.3.1 General
  - 5.10.6.4 Connectors
- 5.10.7 Lighting and socket outlets
- 5.10.8 Control of the supply for lighting and socket outlets
- 5.10.9 Protective earthing
- 5.10.10 Electrical identification
- 5.11 Protection against electric faults; failure analysis; electric safety devices
  - 5.11.1 Protection against electric faults; failure analysis
    - 5.11.1.1 General
  - 5.11.2 Electric safety devices
    - 5.11.2.1 General provisions
    - 5.11.2.2 Safety contacts
      - 5.11.2.2.1 General
      - 5.11.2.2.3 Safety circuits
        - 5.11.2.2.3.1 General
      - 5.11.2.2.4 Operation of electric safety devices
      - 5.11.2.2.5 Actuation of electric safety devices
      - 5.11.2.2.6 Programmable electronic systems in safety related applications (PESSRAL)
  - 5.11.2.3 Safety circuits
    - 5.11.2.3.1 General
  - 5.11.2.4 Operation of electric safety devices
  - 5.11.2.5 Actuation of electric safety devices
  - 5.11.2.6 Programmable electronic systems in safety related applications (PESSRAL)
- 5.12 Controls — Final limit switches — Priorities
  - 5.12.1 Control of lift operations
    - 5.12.1.1 Control of normal operation
    - 5.12.1.2 Load control
    - 5.12.1.3 Monitoring the normal slowdown of the machine in case of reduced buffer stroke
    - 5.12.1.4 Control of levelling, re-levelling and preliminary operation with doors not closed and locked
    - 5.12.1.5 Control of inspection operation
      - 5.12.1.5.1 Design requirements
      - 5.12.1.5.2 Functional requirements:
        - 5.12.1.5.2.1 Inspection operation switch
        - 5.12.1.5.2.2 Return-to-normal operation of the lift
        - 5.12.1.5.2.3 Push buttons
        - 5.12.1.5.2.4 Inspection control station(s)
    - 5.12.1.6 Control of emergency electrical operation
  - 5.12.1.7 Protection for maintenance operations
  - 5.12.1.8 Landing and car door bypass device
  - 5.12.1.9 Prevention of normal operation of the lift with faulty door contact circuits
  - 5.12.1.10 Electrical anti-creep system (see Table 12)
  - 5.12.1.11 Stopping devices
- 5.12.2 Final limit switches
  - 5.12.2.1 General
  - 5.12.2.2 Actuation of the final limit switches
  - 5.12.2.3 Method of operation of final limit switches
- 5.12.3 Emergency alarm device and intercom system
- 5.12.4 Priorities and signals

## 6 Verification of the safety requirements and/or protective measures

- 6.1 Technical compliance documentation
- 6.2 Verification of design
- 6.3 Examinations and tests before putting into service
  - 6.3.1 Braking system (5.9.2.2)
  - 6.3.2 Electric installation
  - 6.3.3 Checking of the traction (5.5.3)
  - 6.3.4 Car safety gear (5.6.2)
  - 6.3.5 Counterweight or balancing weight safety gear (5.6.2)
  - 6.3.6 Pawl device (5.6.5)

- 6.3.7 Buffers (5.8.1, 5.8.2)
  - 6.3.8 Rupture valve (5.6.3)
  - 6.3.9 Restrictor/one-way restrictor (5.6.4)
  - 6.3.10 Pressure test
  - 6.3.11 Ascending car overspeed protection means (5.6.6)
  - 6.3.12 Stopping of the car at landings and levelling accuracy (5.12.1.1.4)
  - 6.3.13 Protection against unintended car movement (5.6.7)
  - 6.3.14 Protection against falling/shearing (5.3.9.3.4)
- 7 Information for use**
- 7.1 General
  - 7.2 Instruction manual
    - 7.2.1 General
    - 7.2.2 Normal use
    - 7.2.3 Maintenance
    - 7.2.4 Examinations and tests
  - 7.3 Logbook
- 8 Use of ISO/TS 8100-3**
- Annex A (normative) List of the electric safety devices**
- Annex B (informative) Technical compliance documentation**
- Annex C (informative) Periodic examinations and tests, examinations and tests after an important modification or after an accident**
- C.1 Periodic examinations and tests
  - C.2 Examinations and tests after an important modification or after an accident
- Annex D (informative) Machinery spaces — Access**
- Annex E (informative) Building interfaces**
- E.1 General provisions
  - E.2 Support of guide rails
  - E.3 Ventilation of car, well and machine rooms
    - E.3.1 General
    - E.3.2 Ventilation of the well and car
    - E.3.3 Ventilation of machine rooms
- Annex F (normative) Pit access ladder**
- F.1 Types of pit access ladder
  - F.2 General provisions
  - F.3 Ladder uprights and rungs
    - F.3.1 Ladder uprights
    - F.3.2 Ladder rungs
  - F.4 Specific provisions for non-fixed type ladders
  - F.5 Location of the ladder in the pit
- Annex G (informative) Relationship between this document and ISO 8100-20**