

# ISO 6358-2:2019 (E)

## Pneumatic fluid power — Determination of flow-rate characteristics of components using compressible fluids — Part 2: Alternative test methods

---

### Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols and units
5	Test installation
5.1	Test circuit for discharge test
5.2	Test circuit for charge test
5.3	General requirements
5.4	Requirements for the tank (item 4)
5.4.1	Structure
5.4.2	Stuffed material
5.4.3	Volume
5.5	Special requirements
6	Test procedures
6.1	Test conditions
6.1.1	Test fluid
6.1.2	Checks
6.1.3	Test measurements
6.2	Measuring procedures
6.2.1	Requirements for testing to publish catalogue ratings
6.2.2	Selection of measuring procedure
6.2.3	Measuring procedures for discharge test
6.2.4	Measuring procedures for charge test (see Figure 2)
6.3	Calculation of characteristics
6.3.1	Sonic conductance, $C$
6.3.1.1	Smoothing of pressure in the tank, $p_3$
6.3.1.2	Conductance characteristics curve
6.3.1.3	Calculation of sonic conductance, $C$
6.3.2	Critical back-pressure ratio, $b$ , and subsonic index, $m$
6.3.3	Pressure dependence coefficient, $K_p$
7	Presentation of test results
8	Identification statement (reference to this document)
Annex A	(informative) Evaluation of measurement uncertainty
A.1	General
A.2	Evaluation of measurement uncertainty of the sonic conductance, $C$ , using Type B
A.2.1	Measurand conductance, $C_e$
A.2.2	Identification of uncertainty of input quantities
A.2.3	Sensitivity coefficient
A.2.4	Expression of absolute standard uncertainty
A.3	Evaluation of measurement uncertainty of the sonic conductance, $C$ , using Type A
A.3.1	Measurand sonic conductance, $C$

- A.3.2 Expression of standard uncertainty
- A.4 Evaluation of measurement uncertainty of the critical back-pressure ratio,  $b$ , and subsonic index,  $m$ , using Type B
  - A.4.1 Measurands
  - A.4.2 Identification and expression of uncertainty
  - A.5 Repeatability and reproducibility
  - A.6 Practical uncertainty due to tank volume
  - A.7 Practical uncertainty due to temperature
  - A.8 Error due to transient change of temperature
- Annex B (normative) Test method to determine and calibrate the volume of an isothermal tank
  - B.1 Test circuit
  - B.2 General requirements
  - B.3 Measurement procedures
  - B.4 Calculation of tank volume
  - B.5 Evaluation of measurement uncertainty of the volume of isothermal tank (Type B of the GUM)
    - B.5.1 Measurand volume  $V_i$
    - B.5.2 Identification of uncertainty of input quantities
    - B.5.3 Sensitivity coefficient
    - B.5.4 Expression of absolute standard uncertainty
    - B.6 Example of test result
- Annex C (informative) Isothermal tank stuffing
  - C.1 General
  - C.2 Mass density and isothermal performance of stuffed material
  - C.3 Stuffed material
- Annex D (informative) Test method to determine isothermal performance
  - D.1 Purpose
  - D.2 Test circuit
  - D.3 Test procedure
  - D.4 Confirmation of isothermalization
- Annex E (informative) Formulae for calculation of flow-rate characteristics
  - E.1 Formulae for discharge test
    - E.1.1 Calculation model
    - E.1.2 Calculation of mass flow rate,  $q_m$
    - E.1.3 Calculation of critical back-pressure ratio,  $b$ , and subsonic index,  $m$
  - E.2 Formulae for charge test
    - E.2.1 Calculation model
    - E.2.2 Calculation of mass flow rate,  $q_m$
    - E.2.3 Calculation of critical back-pressure ratio,  $b$ , and subsonic index,  $m$
- Annex F (informative) Procedures for calculating critical back-pressure ratio,  $b$ , and subsonic index,  $m$ , by the least-square method using the Solver function in Microsoft Excel®2 2 Microsoft Excel is an example of a suitable product(s) available commercially. This information is given for the convenience of users of this document and does not constitute an endorsement by ISO of this product.
  - F.1 Using data in the subsonic flow region
  - F.2 Using the Solver function built in Microsoft Excel
    - F.2.1 Function
    - F.2.2 Calculation of critical back-pressure ratio,  $b$ , and subsonic index,  $m$