

ISO 6336-1:2019-11 (E)

Calculation of load capacity of spur and helical gears - Part 1: Basic principles, introduction and general influence factors

Contents		Page
Foreword		vi
Introduction		vii
1	Scope	1
2	Normative references	2
3	Terms, definitions, symbols and abbreviated terms	2
3.1	Terms and definitions	2
3.2	Symbols and abbreviated terms	2
4	Basic principles	11
4.1	Application	11
4.1.1	Surface durability (pitting)	11
4.1.2	Tooth bending strength	11
4.1.3	Tooth flank fracture	12
4.1.4	Strength and quality of materials	12
4.1.5	Service life under variable load	12
4.1.6	Scuffing	12
4.1.7	Wear	12
4.1.8	Micropitting	12
4.1.9	Plastic-yielding	12
4.1.10	Specific applications	12
4.1.11	Safety factors	13
4.1.12	Testing	15
4.1.13	Manufacturing tolerances	15
4.1.14	Implied accuracy	15
4.1.15	Other considerations	15
4.1.16	Influence factors	16
4.1.17	Numerical formulae	18
4.1.18	Succession of factors in the course of calculation	18
4.1.19	Determination of allowable values of gear deviations	18
4.2	Tangential load, torque and power	18
4.2.1	General	18
4.2.2	Nominal tangential load, nominal torque and nominal power	19
4.2.3	Equivalent tangential load, equivalent torque and equivalent power	19
4.2.4	Maximum tangential load, maximum torque and maximal power	19
5	Application factor, KA	19
5.1	General	19
5.2	Method A -- Factor KA-A	20
5.2.1	Factor KA-A	20
5.2.4	Factor KFFA-A for tooth flank fracture along ISO/TS 6336-4	20
5.2.5	Factor KA-A for scuffing along ISO/TS 6336-20/ISO/TS 6336-21	21
5.2.6	Factor KA-A for micropitting along ISO/TS 6336-22	21
5.3	Method B -- Factor KA-B	21
5.3.1	General	21
5.3.2	Guide values for application factor, KA-B	21
6	Internal dynamic factor, Kv	24

6.1	General	24
6.2	Parameters affecting internal dynamic load and calculations	24
6.2.1	Design	24
6.2.2	Manufacturing	24
6.2.3	Transmission perturbation	25
6.2.4	Dynamic response	25
6.2.5	Resonances	25
6.2.6	Application of internal dynamic factor for low loaded gears	26
6.3	Principles and assumptions	26
6.4	Methods for determination of dynamic factor	27
6.4.1	Method A -- Factor Kv-A	27
6.4.2	Method B -- Factor Kv-B	27
6.4.3	Method C -- Factor Kv-C	27
6.5	Determination of dynamic factor using Method B: Kv-B	28
6.5.1	General	28
6.5.2	Running speed ranges	28
6.5.3	Determination of resonance running speed (main resonance) of a gear pair	29
6.5.4	Dynamic factor in subcritical range ($N < N_{NS}$)	31
6.5.5	Dynamic factor in main resonance range ($N_{NS} < N < 1,15$)	34
6.5.6	Dynamic factor in supercritical range ($N > 1,5$)	34
6.5.7	Dynamic factor in intermediate range ($1,15 < N < 1,5$)	34
6.5.8	Resonance speed determination for specific gear designs	35
6.5.9	Calculation of reduced mass of gear pair with external teeth	37
6.6	Determination of dynamic factor using Method C: Kv-C	38
6.6.1	General	38
6.6.2	Graphical values of dynamic factor using Method C	39
6.6.3	Determination by calculation of dynamic factor using Method C	42
7	Face load factors, KH and KF	43
7.1	Gear tooth load distribution	43
7.2	General principles for determination of face load factors, KH and KF	43
7.2.1	General	43
7.2.2	Face load factor for contact stress, KH	44
7.2.3	Face load factor for tooth root stress, KF	44
7.3	Methods for determination of face load factor -- Principles, assumptions	44
7.3.1	General	44
7.3.2	Method A -- Factors KH-A and KF-A	44
7.3.3	Method B -- Factors KH-B and KF-B	45
7.3.4	Method C -- Factors KH-C and KF-C	45
7.4	Determination of face load factor using Method B: KH-B	45
7.4.1	Number of calculation points	45
7.4.2	Definition of KH	45
7.4.3	Stiffness and elastic deformations	45
7.4.4	Static displacements	49
7.4.5	Assumptions	49
7.4.6	Computer program output	49
7.5	Determination of face load factor using Method C: KH-C	49
7.5.1	General	49
7.5.2	Effective equivalent misalignment, F_y	51
7.5.3	Running-in allowance, y , and running-in factor,	51
7.5.4	Mesh misalignment, f_{ma}	61
7.5.5	Component of mesh misalignment caused by case deformation, f_{ca}	63
7.5.6	Component of mesh misalignment caused by shaft displacement, f_{be}	63
7.6	Determination of face load factor for tooth root stress using Method B or C: KF	64
8	Transverse load factors KH and KF	65
8.1	Transverse load distribution	65
8.2	Determination methods for transverse load factors -- Principles and assumptions	65
8.2.1	General	65
8.2.2	Method A -- Factors KH-A and KF-A	65
8.2.3	Method B -- Factors KH-B and KF-B	66

8.3	Determination of transverse load factors using Method B -- KH-B and KF-B	66
8.3.1	General	66
8.3.2	Determination of transverse load factor by calculation	66
8.3.3	Transverse load factors from graphs	67
8.3.4	Limiting conditions for KH	67
8.3.5	Limiting conditions for KF	67
8.3.6	Running-in allowance, y	68
9	Tooth stiffness parameters, c and c	71
9.1	Stiffness influences	71
9.2	Determination methods for tooth stiffness parameters -- Principles and assumptions	71
9.2.1	General	71
9.2.2	Method A -- Tooth stiffness parameters c _A and c-A	72
9.2.3	Method B -- Tooth stiffness parameters c _B and c-B	72
9.3	Determination of tooth stiffness parameters, c and c, according to Method B	72
9.3.1	General	72
9.3.2	Single stiffness, c	73
9.3.3	Mesh stiffness, c	77
10	Parameter of Hertzian contact	77
10.1	Local radius of relative curvature	77
10.2	Reduced modulus of elasticity, E _r	78
10.3	Local Hertzian contact stress, p _{dyn,CP}	78
10.3.1	Method A	78
10.3.2	Method B	79
10.4	Half of the Hertzian contact width, b _H	80
10.5	Load distribution along the path of contact	80
10.5.1	Definition of contact points, CP, on the path of contact	80
10.5.2	Load sharing factor, XCP	82
10.6	Sum of tangential velocity, v,CP	90
11	Lubricant parameters at given temperature	91
11.1	General	91
11.2	Kinematic viscosity at a given temperature, v	91
11.3	Density of the lubricant at a given temperature ,	92
Annex A (normative) Additional methods for determination of f _{sh} and f _{ma}		93
Annex B (informative) Guide values for crowning and end relief of teeth of cylindrical gears		96
Annex C (informative) Guide values for KH-C for crowned teeth of cylindrical gears		99
Annex D (informative) Derivations and explanatory notes		102
Annex E (informative) Analytical determination of load distribution		106
Annex F (informative) General symbols used for calculation of load capacity of spur and helical gears		128
Bibliography		133