ISO 6336-2:2019-11 (E)

Calculation of load capacity of spur and helical gears - Part 2: Calculation of surface durability (pitting)

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Terms,definitions,symbolsandabbreviatedterms 2
3.1 Terms and definitions 2
3.2 Symbols and abbreviated terms 2

4 Pitting damage and safety factors 6

5 Basic formulae 7
5.1 General 7
5.2 Safety factor for surface durability (against pitting), SH 8
5.3 Contact stress, H 8
5.4 Permissible contact stress, HP 9
5.4.1 General 9
5.4.2 Determination of permissible contact stress, HP -- Principles, assumptions and application 10
5.4.3 Permissible contact stress, HP: Method B 10
5.4.4 Permissible contact stress for limited and long life: Method B 11

6 Zone factor, ZH, and contact factors, ZB and ZD 13
6.1 General 13
6.2 Zone factor, ZH 14
6.2.1 General 14
6.2.2 Graphical values 14
6.2.3 Determination by calculation 14
6.3 Contact factors, ZB and ZD, for 2 14
6.4 Contact factors, ZB and ZD, for > 2 17

7 Elasticity factor, ZE 17

8 Contact ratio factor, Z 18
8.1 General 18
8.2 Determination of contact ratio factor, Z 18
8.2.1 Graphical values 18
8.2.2 Determination by calculation 19
8.3 Calculation of transverse contact ratio, , and overlap ratio, ... 20
8.3.1 Transverse contact ratio, ... 20
8.3.2 Overlap ratio, ... 20

9 Helix angle factor, Z 21

10 Strength for contact stress 21
10.1 General 21
10.2 Allowable stress numbers (contact), H lim: Method B 21
10.3 Allowable stress number values: Method BR 22

11 Life factor, ZNT(forflanks) 22
11.1 General 22
11.2 Life factor, ZNT: Method A 22
11.3 Life factor, ZNT: Method B 22

12 Influenceoflubricantfilm,factorsZL, Zv and ZR 24
12.1 General 24
12.2 Influence of lubricant film: Method A 24
12.3 Influence of lubricant film, factors ZL, Zv and ZR: Method B 24
12.3.1 General 24

12.3.2 Factors ZL, Zv and ZR for reference stress 25
12.3.3 Factors ZL, Zv and ZR for static stress 30

13 Workhardeningfactor,ZW 30
13.1 General 30
13.2 Work hardening factor, ZW: Method A 30
13.3 Work hardening factor, ZW: Method B 31
13.3.1 Surface-hardened steel pinion with through-hardened steel gear 31
13.3.2 Through-hardened steel pinion with through-hardened steel gear 33
13.3.3 Surface-hardened steel pinion with ductile iron gear 34

14 Size factor, ZX 36

Bibliography 37