

ISO 10303-510:2000-03 (E)

Industrial automation systems and integration - Product data representation and exchange - Part 510: Application interpreted construct: Geometrically bounded wireframe

| Contents | | Page |
|---|--|-------------|
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Definitions and abbreviations | 2 |
| 3.3 | Abbreviations | 3 |
| 4 | EXPRESS short listing | 3 |
| 4.1 | Introduction | 4 |
| 4.2 | Fundamental concepts and assumptions | 4 |
| 4.3 | aic_geometrically_bounded_wireframe entity definition: geometrically_bounded_wireframe_shape_representation | 5 |
| 4.4 | aic_geometrically_bounded_wireframe function definitions | 7 |
| 4.4.1 | valid_geometrically_bounded_wf_curve | 7 |
| 4.4.2 | valid_geometrically_bounded_wf_point | 8 |
| Annex A (normative) Short names of entities | | 10 |
| Annex B (normative) Information object registration | | 11 |
| B.1 | Document identification | 11 |
| B.2 | Schema identification | 11 |
| Annex C (informative) EXPRESS-G diagrams | | 12 |
| Annex D (informative) Computer interpretable listings | | 19 |
| Index | | 20 |
| Figures Figure C.1 - aic_geometrically_bounded_wireframe - EXPRESS-G diagram 1 of 6 | | 13 |
| Figure C.2 - aic_geometrically_bounded_wireframe - EXPRESS-G diagram 2 of 6 | | 14 |
| Figure C.3 - aic_geometrically_bounded_wireframe - EXPRESS-G diagram 3 of 6 | | 15 |
| Figure C.4 - aic_geometrically_bounded_wireframe - EXPRESS-G diagram 4 of 6 | | 16 |
| Figure C.5 - aic_geometrically_bounded_wireframe - EXPRESS-G diagram 5 of 6 | | 17 |
| Figure C.6 - aic_geometrically_bounded_wireframe - EXPRESS-G diagram 6 of 6 | | 18 |
| Tables Table A.1 - Short names of entities | | 10 |