

# ISO/TS 14521:2020-04 (E)

## Gears - Calculation of load capacity of worm gears

---

Contents	Page
<b>Foreword</b>	vi
<b>Introduction</b>	vii
<b>1 Scope</b>	1
<b>2 Normative references</b>	1
<b>3 Terms, definitions and symbols</b>	1
3.1 Terms and definitions	1
3.2 Symbols	2
<b>4 General consideration</b>	7
4.1 Worm gear load capacity rating criteria	7
4.2 Basis of the method	8
4.3 Concept of absolute and relative parameters	8
4.4 Applicability	9
4.5 Validity	10
4.6 System considerations	11
4.7 Calculation methods A, B, C	11
4.7.1 Generality on methods A, B and C	11
4.7.2 Notes on numerical formulae	12
4.7.3 Base conditions, interaction	12
4.7.4 Other notes	13
4.8 Standard reference gear	13
<b>5 Required date for calculation</b>	13
5.1 Input variable	13
5.2 Safety factors	15
<b>6 Forces, speeds and parameters for the calculation of stresses</b>	15
6.1 General	15
6.2 Tooth forces	15
6.2.1 Application factor	15
6.2.2 Dynamic factor	15
6.2.3 Load distribution factor	15
6.2.4 Tooth force components	16
6.3 Sliding velocity at reference diameter	17
6.4 Physical parameters	17
6.4.1 Generality on physical parameters	17
6.4.2 Parameter for the mean Hertzian stress	18
6.4.3 Parameter for the mean lubricant film thickness	19
6.4.4 Parameter for the mean sliding path	20
6.5 Calculation of mean contact stress	21
6.6 Calculation of mean lubricant film thickness	22
6.7 Calculation of the wear path	23
6.8 Calculation of the lubricant kinematic viscosity	23
<b>7 Efficiency and power loss</b>	23
7.1 General	23
7.2 Total efficiency	24
7.2.1 Method A	24
7.2.2 Method B	24

7.3	Total power loss .....	24
7.3.1	Methods of calculation .....	24
7.3.2	Idle running power loss .....	25
7.3.3	Bearing load power loss .....	25
7.3.4	Sealing power loss .....	25
7.3.5	Adaptation of the calculation procedure to a specific test .....	26
7.4	Gear efficiency .....	26
7.4.1	Efficiency calculation .....	26
7.4.2	Base coefficient of friction, $\mu_{OT}$ , of the standard reference gear .....	26
7.4.3	Size factor .....	28
7.4.4	Geometry factor .....	29
7.4.5	Material factor .....	29
7.4.6	Roughness factor .....	29
7.4.7	Adaptation of the calculation procedure to a specific test .....	29
7.5	Meshing power loss .....	30
7.5.1	Method A .....	30
7.5.2	Method B .....	30
7.5.3	Method C .....	30
<b>8</b>	<b>Wear load capacity .....</b>	<b>30</b>
8.1	General .....	30
8.2	Wear safety factor .....	30
8.3	Expected wear .....	31
8.3.1	Method A .....	31
8.3.2	Methods B, C .....	31
8.4	Permissible wear .....	35
8.5	Adaptation of the calculation procedure to a specific test .....	36
<b>9</b>	<b>Surface durability (pitting resistance) .....</b>	<b>36</b>
9.1	General .....	36
9.2	Pitting safety factor .....	36
9.3	Actual contact stress .....	37
9.3.1	Method A .....	37
9.3.2	Methods B, C .....	37
9.4	Limiting value of contact stress .....	37
9.5	Adaptation of the calculation procedure to specific test .....	38
<b>10</b>	<b>Deflection .....</b>	<b>38</b>
10.1	General .....	38
10.2	Deflection safety factor .....	39
10.3	Actual deflection .....	39
10.3.1	Method A .....	39
10.3.2	Method B .....	39
10.3.3	Method C .....	39
10.4	Limiting value of deflection .....	40
<b>11</b>	<b>Tooth root strength .....</b>	<b>40</b>
11.1	Safety factor for tooth breakage .....	40
11.2	Actual tooth root stress .....	40
11.2.1	Method A .....	40
11.2.2	Method B .....	40
11.2.3	Method C .....	40
11.3	Limiting value of shear stress at tooth root .....	42
11.3.1	General .....	42
11.3.2	Shear endurance limit, $\tau_{F\lim T}$ .....	42
11.3.3	Life factor, $Y_{NL}$ .....	42
11.4	Adaptation of the calculation procedure to a specific test .....	44
<b>12</b>	<b>Temperature safety factor .....</b>	<b>44</b>
12.1	Temperature safety factor for splash lubrication .....	44
12.1.1	General .....	44
12.1.2	Determination of oil sump temperature .....	45
12.1.3	Limiting values .....	46
12.2	Temperature safety factor for oil spray lubrication .....	46
12.2.1	General .....	46
12.2.2	Cooling capacity $P_K$ .....	46
<b>13</b>	<b>Determination of the wheel bulk temperature .....</b>	<b>47</b>

13.1	Wheel bulk temperature with splash lubrication.....	47
13.1.1	General.....	47
13.1.2	Method A.....	48
13.1.3	Method B.....	48
13.1.4	Method C.....	48
13.2	Wheel bulk temperature with spray lubrication.....	48
13.2.1	General.....	48
13.2.2	Method A.....	48
13.2.3	Method B.....	48
13.2.4	Method C.....	49
<b>Annex A</b>	(informative) Notes on physical parameters.....	<b>50</b>
<b>Annex B</b>	(normative) Methods for the determination of the parameters.....	<b>51</b>
<b>Annex C</b>	(normative) Lubricant film thickness according to the Elasto Hydrodynamic Lubrication (EHL) theory .....	<b>56</b>
<b>Annex D</b>	(normative) Wear path definition.....	<b>58</b>
<b>Annex E</b>	(informative) Notes on calculation wear .....	<b>61</b>
<b>Annex F</b>	(informative) Notes on tooth root strength.....	<b>62</b>
<b>Annex G</b>	(informative) Adaptation of formulae for the reference gear with results from testing.....	<b>63</b>
<b>Annex H</b>	(informative) Life time estimation for worm gears with a high risk of pitting damage .....	<b>66</b>
<b>Annex I</b>	(informative) Examples.....	<b>68</b>
<b>Annex J</b>	(informative) Examples of limit load capacity in a range of working conditions .....	<b>84</b>
<b>Bibliography</b>	.....	<b>87</b>