

ISO 4156-3:2021 (E)

Straight cylindrical involute splines — Metric module, side fit — Part 3: Inspection

Contents

| | |
|---------|--|
| | Foreword |
| | Introduction |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Symbols and abbreviated terms |
| 5 | Reference conditions |
| 6 | Quality features |
| 6.1 | General |
| 6.2 | Size |
| 6.2.1 | Actual size |
| 6.2.2 | Effective size |
| 6.3 | Location |
| 6.4 | Form |
| 7 | Methods of inspection |
| 7.1 | Size |
| 7.1.1 | General methods |
| 7.1.2 | Choice of measuring instrument |
| 7.1.3 | Actual size |
| 7.1.3.1 | Dimensions over and between balls |
| 7.1.3.2 | Dimensions over and between pins |
| 7.1.3.3 | NO GO sector gauge |
| 7.1.3.4 | Span size over k teeth |
| 7.1.3.5 | Variable sector gauge |
| 7.1.4 | Effective size |
| 7.1.4.1 | GO composite gauge |
| 7.1.4.2 | Variable composite gauge |
| 7.1.4.3 | NO GO composite gauge |
| 7.1.4.4 | Inspection of diameter at tooth tip (Dii or Dee) |
| 7.2 | Location |
| 7.2.1 | General |
| 7.2.2 | Choice of the method of inspection of location |
| 7.2.3 | Effective axis using mating part |
| 7.2.4 | Actual pitch cylinder axis |
| 7.2.5 | Calculation with Fourier analysis |
| 7.2.6 | Spline clamping system |
| 7.3 | Form |
| 8 | Measurements with balls or pins |
| 8.1 | General |
| 8.2 | Selection of balls or pins |
| 8.3 | Use and marking of pins |
| 8.4 | Statistical actual tolerance limit LSTA |
| 8.4.1 | General |
| 8.4.2 | Acceptance of parts according to the statistical actual tolerance limit LSTA |

- 8.4.3 Examples
- 8.5 Calculation of ball or pin diameter (DRe or DRi)
- 8.5.1 External spline
- 8.5.2 Internal spline
- 8.6 Calculation of dimensions for ball or pin inspection (part and gauge inspection)
- 8.6.1 Exact calculation
- 8.6.1.1 Measurement over two balls or pins — External splines (MRe)
- 8.6.1.2 Measurement between two pins — Internal splines (MRi)
- 8.6.2 Approximation factor
- 8.6.2.1 General
- 8.6.2.2 Calculation of the approximation factor Ke
- 8.6.2.3 Calculation of the approximation factor Ki
- 9 Measurement over k teeth — External splines (W)
 - 9.1 Calculation of W
 - 9.2 Choice of k
- 10 Gauges
 - 10.1 Generalities
 - 10.1.1 Conditions of use of gauges
 - 10.1.1.1 GO gauge
 - 10.1.1.2 NO GO sector gauge
 - 10.1.1.3 NO GO composite gauge
 - 10.1.2 Limiting dimensions of use for gauges
 - 10.1.3 Handles of spline gauges
 - 10.1.4 Number of teeth for sector NO GO gauges
 - 10.2 Length of measuring part of gauges
 - 10.2.1 Influence of the active spline length and of the length of engagement
 - 10.2.2 GO or NO GO gauges
 - 10.2.3 Master plug gauges
 - 10.2.4 Spline gauges of pitch diameters $D > 180$ mm
 - 10.3 Manufacturing tolerances for spline gauges
 - 10.4 Values of deviation allowances of spline gauges
 - 10.5 Inspection of gauges
 - 10.5.1 Damage
 - 10.5.2 Marking
 - 10.5.3 Major diameter of plug gauges and minor diameter of ring gauges
 - 10.5.4 Form diameter
 - 10.5.5 Tooth thickness of plug gauges
 - 10.5.6 Space width of ring gauges
 - 10.5.7 Form deviations
 - 10.5.8 Gauge wear inspection
 - 10.5.9 Inspection certificates
 - 10.6 Dimensions, designation and marking of gauges
 - 10.6.1 Inspection of external splines
 - 10.6.1.1 GO composite ring gauge
 - 10.6.1.2 Tapered tooth master plug gauge for GO composite ring gauge
 - 10.6.1.3 NO GO sector ring gauge
 - 10.6.1.4 Tapered tooth master plug gauge for NO GO sector ring gauge
 - 10.6.1.5 NO GO composite ring gauge
 - 10.6.1.6 Tapered tooth master plug gauge for NO GO composite ring gauge
 - 10.6.2 Inspection of internal splines
 - 10.6.2.1 GO composite plug gauge
 - 10.6.2.2 NO GO sector plug gauge
 - 10.6.2.3 NO GO composite plug gauge
 - 10.6.3 Inspection with plain gauges for internal and external splines
 - 10.6.3.1 General
 - 10.6.3.2 Inspection of minor diameter — Internal spline
 - 10.6.3.3 Inspection of major diameter — External spline
 - 10.6.4 Marking of gauges
- 11 Measurement of spline deviations
 - 11.1 General
 - 11.2 Total profile deviation $F\alpha$

- 11.3 Total pitch deviation F_p
- 11.4 Total helix deviation F_β

Annex A (informative) Influences of eccentricity and pitch deviation as explained in ISO 4156:1981

Page count: 47