

# ISO/TS 10300-20:2021 (E)

## Calculation of load capacity of bevel gears — Part 20: Calculation of scuffing load capacity — Flash temperature method

---

### Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols
5	Virtual cylindrical gear
5.1	General
5.2	Local geometry parameters
5.2.1	Transverse path of contact
5.2.2	Length of contact lines
5.2.3	Local equivalent radius of curvature, $\rho_{el}, Y$
5.2.4	Local load sharing factor, $X_{LS}, Y$
6	Stresses and velocities
6.1	Local modified contact stress, $\sigma_{H, mod}, Y$
6.2	Sliding and sum of velocities
6.3	Local relative lubricating film thickness, $\lambda_z, Y$
6.4	Local coefficient of friction, $\mu_Y$
7	Local contact temperature, $\theta_C, Y$
7.1	General
7.2	Power losses influencing the bulk temperature
7.2.1	General
7.2.2	Method A
7.2.3	Method B
7.2.4	Method C
7.3	Bulk temperature, $\theta_M$
7.3.1	General
7.3.2	Method A
7.3.3	Method B
7.3.4	Tip relief factor, $X_{CA}$
7.4	Local flash temperature, $\theta_{fl}, Y$
8	Permissible contact temperature
8.1	Limit temperature from scuffing test, $\theta_{S, DIN}$
8.2	Permissible temperature, $\theta_{SC}$
8.3	Permissible scuffing temperature, $\theta_{S}, Y$
9	Local safety factor, $SS, Y$