

DIN EN ISO 16890-2:2023-12 (E)

Air filters for general ventilation - Part 2: Measurement of fractional efficiency and air flow resistance (ISO 16890-2:2022)

| Contents | | Page |
|--------------------------------|--|-------------|
| European foreword | | 5 |
| Foreword | | 6 |
| Introduction | | 8 |
| 1 | Scope | 10 |
| 2 | Normative references | 10 |
| 3 | Terms and definitions | 10 |
| 3.1 | Air flow and resistance | 11 |
| 3.2 | Test device | 11 |
| 3.3 | Aerosol | 11 |
| 3.4 | Particle counter | 12 |
| 3.5 | Efficiency | 12 |
| 3.6 | Other terms | 13 |
| 4 | Symbols and abbreviated terms | 13 |
| 4.1 | Symbols | 13 |
| 4.2 | Abbreviated terms | 15 |
| 5 | General test requirements | 15 |
| 5.1 | Test device requirements | 15 |
| 5.2 | Test device installation | 15 |
| 5.3 | Test rig requirements | 16 |
| 6 | Test materials | 16 |
| 6.1 | Liquid phase aerosol | 16 |
| 6.1.1 | DiEthylHexylSebacate (DEHS) test aerosol | 16 |
| 6.1.2 | DEHS properties | 16 |
| 6.1.3 | Liquid phase aerosol generation | 16 |
| 6.2 | Solid phase aerosol | 17 |
| 6.2.1 | Potassium chloride (KCl) test aerosol | 17 |
| 6.2.2 | KCl properties | 17 |
| 6.2.3 | Solid phase aerosol generation | 18 |
| 6.3 | Reference aerosols | 19 |
| 6.3.1 | Reference aerosol for 0,3 µm to 1,0 µm | 19 |
| 6.3.2 | Reference aerosol for 1,0 µm to 10,0 µm | 19 |
| 6.4 | Aerosol loading | 19 |
| 7 | Test equipment | 20 |
| 7.1 | Test rig | 20 |
| 7.1.1 | Dimensions | 20 |
| 7.1.2 | Construction materials | 20 |
| 7.1.3 | Test rig shape | 21 |
| 7.1.4 | Test rig air supply | 21 |
| 7.1.5 | Test rig isolation | 21 |
| 7.1.6 | D/S mixing orifice | 21 |
| 7.1.7 | Aerosol sampling | 22 |
| 7.1.8 | Test rig air flow rate measurement | 24 |
| 7.1.9 | Resistance to air flow measurement | 24 |
| 7.1.10 | Test devices not measuring 610 mm × 610 mm (24.0 inches × 24.0 inches) | 25 |
| 7.1.11 | Dust injection testing | 25 |
| 7.2 | Aerosol particle counter | 26 |
| 7.2.1 | General | 26 |
| 7.2.2 | OPC sampled size range | 26 |
| 7.2.3 | OPC particle size ranges | 26 |
| 7.2.4 | Sizing resolution | 27 |
| 7.2.5 | Calibration | 27 |

| | | | |
|-----------|--------|--|-----------|
| | 7.2.6 | Air flow rate..... | 27 |
| | 7.2.7 | Zero counting..... | 27 |
| | 7.2.8 | Dual OPC(s)..... | 27 |
| | 7.3 | Temperature, relative humidity..... | 27 |
| 8 | | Qualification of test rig and apparatus..... | 28 |
| | 8.1 | Schedule of qualification testing requirements..... | 28 |
| | 8.1.1 | General..... | 28 |
| | 8.1.2 | Qualification testing..... | 28 |
| | 8.1.3 | Qualification documentation..... | 28 |
| | 8.2 | Qualification testing..... | 29 |
| | 8.2.1 | Test rig — Pressure system testing..... | 29 |
| | 8.2.2 | OPC — Air flow rate stability test..... | 30 |
| | 8.2.3 | OPC — Zero test..... | 30 |
| | 8.2.4 | OPC — Sizing accuracy..... | 30 |
| | 8.2.5 | OPC — Overload test..... | 31 |
| | 8.2.6 | Aerosol generator — Response time..... | 31 |
| | 8.2.7 | Aerosol generator — Neutralizer..... | 32 |
| | 8.2.8 | Test rig — Air leakage test..... | 33 |
| | 8.2.9 | Test rig — Air velocity uniformity..... | 33 |
| | 8.2.10 | Test rig — Aerosol uniformity..... | 34 |
| | 8.2.11 | Test rig — Downstream mixing..... | 35 |
| | 8.2.12 | Test rig — Empty test device section pressure..... | 37 |
| | 8.2.13 | Test rig — 100 % efficiency test and purge time..... | 37 |
| | 8.2.14 | Test rig — Correlation ratio..... | 38 |
| | 8.3 | Maintenance..... | 38 |
| | 8.3.1 | General..... | 38 |
| | 8.3.2 | Test rig — Background counts..... | 39 |
| | 8.3.3 | Test rig — Reference filter test..... | 39 |
| | 8.3.4 | Test rig — Pressure reference test..... | 40 |
| | 8.3.5 | Test rig — Final filter resistance..... | 41 |
| 9 | | Test methods..... | 41 |
| | 9.1 | Air flow rate..... | 41 |
| | 9.2 | Measurement of resistance to air flow..... | 41 |
| | 9.3 | Measurement of fractional efficiency..... | 41 |
| | 9.3.1 | Aerosol sampling protocol..... | 41 |
| | 9.3.2 | Background sampling..... | 41 |
| | 9.3.3 | Testing sequence for a single OPC..... | 42 |
| | 9.3.4 | Testing sequence for dual OPC..... | 46 |
| 10 | | Data reduction and calculations..... | 47 |
| | 10.1 | Correlation ratio..... | 47 |
| | 10.1.1 | Correlation ratio general..... | 47 |
| | 10.1.2 | Correlation ratio data reduction..... | 48 |
| | 10.2 | Penetration and fractional efficiency..... | 49 |
| | 10.2.1 | Penetration and fractional efficiency general..... | 49 |
| | 10.2.2 | Penetration data reduction..... | 50 |
| | 10.3 | Data quality requirements..... | 52 |
| | 10.3.1 | Correlation background counts..... | 52 |
| | 10.3.2 | Efficiency background counts..... | 52 |
| | 10.3.3 | Correlation ratio..... | 52 |
| | 10.3.4 | Penetration..... | 53 |
| | 10.4 | Fractional efficiency calculation..... | 54 |
| 11 | | Reporting results..... | 54 |
| | 11.1 | General..... | 54 |
| | 11.2 | Required reporting elements..... | 54 |
| | 11.2.1 | Report general..... | 54 |
| | 11.2.2 | Report values..... | 54 |

| | |
|--|-----------|
| 11.2.3 Report summary | 55 |
| 11.2.4 Report details..... | 56 |
| Annex A (informative) Example..... | 59 |
| Annex B (informative) Resistance to air flow calculation..... | 66 |
| Bibliography..... | 68 |