

ISO/TS 6336-21:2022-05 (E)

Calculation of load capacity of spur and helical gears - Part 21: Calculation of scuffing load capacity - Integral temperature method

Contents		Page
Foreword.....		iv
Introduction.....		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
3.1	Terms and definitions.....	1
3.2	Symbols and units.....	1
4	Field of application	4
4.1	General.....	4
4.2	Scuffing damage.....	4
4.3	Integral temperature criterion.....	5
5	Influence factors	5
5.1	Mean coefficient of friction, μ_{mC}	5
5.2	Run-in factor, X_E	8
5.3	Thermal flash factor, X_M	8
5.4	Pressure angle factor, $X_{\alpha\beta}$	9
6	Calculation	10
6.1	Cylindrical gears.....	10
6.1.1	General.....	10
6.1.2	Scuffing safety factor, S_{intS}	10
6.1.3	Permissible integral temperature, ϑ_{intP}	10
6.1.4	Integral temperature, ϑ_{int}	11
6.1.5	Flash temperature at pinion tooth tip, ϑ_{flaE}	11
6.1.6	Bulk temperature, ϑ_M	11
6.1.7	Mean coefficient of friction, μ_{mC}	12
6.1.8	Run-in factor, X_E	12
6.1.9	Thermal flash factor, X_M	12
6.1.10	Pressure angle factor, $X_{\alpha\beta}$	12
6.1.11	Geometry factor at tip of pinion, X_{BE}	12
6.1.12	Approach factor, X_Q	13
6.1.13	Tip relief factor, X_{Ca}	14
6.1.14	Contact ratio factor, X_ϵ	15
6.2	Scuffing integral temperature.....	17
6.2.1	General.....	17
6.2.2	Scuffing integral temperature, ϑ_{intS}	18
6.2.3	Relative welding factor, X_{WrelT}	22
Annex A	(informative) Examples	23
Annex B	(informative) Contact-time-dependent scuffing temperature	32
Bibliography		37