

ISO/TS 6336-21:2022-05 (E)

Calculation of load capacity of spur and helical gears - Part 21: Calculation of scuffing load capacity - Integral temperature method

Contents

Page

Foreword.....	iv
Introduction.....	v
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	1
3.1 Terms and definitions.....	1
3.2 Symbols and units.....	1
4 Field of application.....	4
4.1 General.....	4
4.2 Scuffing damage.....	4
4.3 Integral temperature criterion.....	5
5 Influence factors.....	5
5.1 Mean coefficient of friction, μ_{mC}	5
5.2 Run-in factor, X_E	8
5.3 Thermal flash factor, X_M	8
5.4 Pressure angle factor, $X_{\alpha\beta}$	9
6 Calculation.....	10
6.1 Cylindrical gears.....	10
6.1.1 General.....	10
6.1.2 Scuffing safety factor, S_{intS}	10
6.1.3 Permissible integral temperature, ϑ_{intP}	10
6.1.4 Integral temperature, ϑ_{int}	11
6.1.5 Flash temperature at pinion tooth tip, ϑ_{flaE}	11
6.1.6 Bulk temperature, ϑ_M	11
6.1.7 Mean coefficient of friction, μ_{mC}	12
6.1.8 Run-in factor, X_E	12
6.1.9 Thermal flash factor, X_M	12
6.1.10 Pressure angle factor, $X_{\alpha\beta}$	12
6.1.11 Geometry factor at tip of pinion, X_{BE}	12
6.1.12 Approach factor, X_Q	13
6.1.13 Tip relief factor, X_{Ca}	14
6.1.14 Contact ratio factor, X_ϵ	15
6.2 Scuffing integral temperature.....	17
6.2.1 General.....	17
6.2.2 Scuffing integral temperature, ϑ_{intS}	18
6.2.3 Relative welding factor, X_{WrelT}	22
Annex A (informative) Examples.....	23
Annex B (informative) Contact-time-dependent scuffing temperature.....	32
Bibliography.....	37