ISO/TS 6336-20:2022-05 (E)

Calculation of load capacity of spur and helical gears - Part 20: Calculation of scuffing load capacity - Flash temperature method

Contents

Page

Foreword ... **iv**

Introduction ... **v**

1 Scope ... **1**

2 Normative references ... **1**

3 Terms and definitions ... **1**
3.1 Terms and definitions ... 1
3.2 Symbols and units ... 1

4 Scuffing and wear ... **5**
4.1 Occurrence of scuffing and wear ... 5
4.2 Transition diagram ... 5
4.3 Friction at incipient scuffing ... 7

5 Basic formulae ... **7**
5.1 Contact temperature ... 7
5.2 Flash temperature formula ... 8
5.3 Transverse unit load ... 10
5.4 Distribution of overall bulk temperatures ... 11
5.5 Rough approximation of a bulk temperature ... 11

6 Coefficient of friction ... **12**
6.1 General ... 12
6.2 Mean coefficient of friction, method A ... 12
6.3 Mean coefficient of friction, method B ... 13
6.4 Mean coefficient of friction, method C ... 13

7 Parameter on the line of action ... **14**

8 Approach factor ... **15**

9 Load sharing factor, X_Γ ... **15**
9.1 General ... 15
9.2 Spur gears with unmodified profiles ... 16
9.3 Spur gears with profile modification ... 17
9.4 Buttressing factor, $X_{\mathrm{but},\Gamma}$ ... 18
9.5 Helical gears with $\varepsilon_\beta \leq 0{,}8$ and unmodified profiles ... 19
9.6 Helical gears with $\varepsilon_\beta \leq 0{,}8$ and profile modification ... 19
9.7 Helical gears with $\varepsilon_\beta \geq 1{,}2$ and unmodified profiles ... 20
9.8 Helical gears with $\varepsilon_\beta \geq 1{,}2$ and profile modification ... 21
9.9 Helical gears with $0{,}8 < \varepsilon_\beta < 1{,}2$ ... 22

10 Scuffing temperature and safety ... **23**
10.1 Scuffing temperature ... 23
10.2 Structural factor ... 23
10.3 Contact exposure time ... 24
10.4 Scuffing temperature in gear tests ... 25
10.5 Safety range ... 25

Annex A (informative) **Flash temperature formula presentation** ... **26**

Annex B (informative) **Optimal profile modification** ... **31**

Bibliography ... **33**