ISO 15086-3:2022-07 (E)

Hydraulic fluid power - Determination of the fluid-borne noise characteristics of components and systems - Part 3: Measurement of hydraulic impedance

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Symbols 2

5 Test conditions and accuracy of instrumentation 3
5.1 Test conditions (permissible variations) 3
5.1.1 General 3
5.1.2 Fluid temperature 4
5.1.3 Fluid density and viscosity 4
5.1.4 Mean fluid pressure 4
5.1.5 Mean flow measurement 4
5.2 Instrumentation precision 4
5.2.1 Steady-state accuracy class 4
5.2.2 Dynamic-state accuracy class 4

6 Measurement of the impedance of a single-port passive component 4
6.1 Local impedance -- Measurement principle 4
6.2 Hydraulic impedance 5
6.2.1 Measurement principle 5
6.2.2 Simplified algorithm for determining the component of the local hydraulic impedance 6
6.3 Factors influencing the accuracy of the impedance measurement 6
6.3.1 General 6
6.3.2 Pulse generator 6
6.3.3 Pressure transfer function measured by the PTx/PT3 pressure transducers and the calibration correction 7
6.3.4 Numerical value of terms A and B of the pipe section admittance matrix used for the indirect determination of the pulsed flows 7
6.4 Measurement of local impedance 9
6.4.1 Test circuit 9
6.4.2 Test procedure 10

7 Measurement of the admittance matrix and impedance matrix of a two-port passive hydraulic component 14
7.1 Definitions and principles of measurement of the admittance matrix and impedance matrix of a two-port passive hydraulic component 14
7.1.1 General 14
7.1.2 Principle of the method of measuring the admittance matrix 14
7.1.3 Algorithm for determining the admittance matrix of a two-port, passive component for identical dimensions of upstream and downstream pipes 17
7.1.4 Measurement result presentation 20

8 Test report 23
8.1 General 23

8.2 General information 23
8.3 Test data 23

9 Identification statement (reference to this document) 24

Bibliography 25