ISO 24477:2022-08 (E)

Vacuum technology - Vacuum gauges - Specifications, calibration and measurement uncertainties for spinning rotor gauges

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms and definitions 1
3.1 Terms related to components 2
3.2 Terms related to physical parameters 2

4 Symbols and abbreviated terms 4

5 Principle of a spinning rotor gauge 4

6 Specifications for spinning rotor gauge 5
6.1 Diameter and density of rotor 5
6.2 Materials of rotor and thimble 5
6.3 Connecting flange of thimble 5
6.4 Leak rate of thimble with flange 5
6.5 Suspension head positioning 5
6.6 Limits of rotor frequency 6
6.7 Warm-up period 6
6.8 Baking temperature 6
6.9 Measurement range 6
6.10 Sampling time 6
6.11 Internal volume 6
6.12 Interface and pin connections of controller 6
6.13 Dimensions and weights of suspension head and controller 6
6.14 Display and signal output 6
6.15 Nominal operating (environment) conditions 6
6.16 Storage and transportation conditions 6
6.17 Input power and electrical requirements 6

7 Additional (optional) specifications for spinning rotor gauge 7
7.1 Long-term instability 7
7.2 Expected measurement uncertainty 7
7.3 Compatibility between a suspension head and a rotor 7
7.4 Inspection record and calibration certificate 7
7.5 Allowed vibration level 7
7.6 Cable length 7
7.7 Photograph 7

8 Calibration 7
8.1 Parameters to be calibrated 7
8.2 Calibration procedures 8
8.2.1 General 8
8.2.2 Calibration method A for eff,0 8
8.2.3 Calibration method B for eff,0 8
8.3 Calibration uncertainty 9

8.4 Calibration certificate 9

9 Measurement uncertainty at use 10

Bibliography 11