ISO 29461-2:2022-08 (E)

Air intake filter systems for rotary machinery - Test methods - Part 2: Filter element endurance test in fog and mist environments

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Symbols and abbreviated terms 3

5 General requirements 4

6 Test conditions 4
6.1 Test air 4
6.2 Test water 4

7 Test rig and equipment 5
7.1 Test rig 5
7.2 Water spray device 6
7.3 Humidifying device 6
7.4 Water collecting groove 6

8 Qualification of test rig and apparatus 6
8.1 Pressure system test 6
8.2 Air leakage test 6
8.3 Air velocity uniformity in the test duct 6
8.4 Pressure drop of test duct with no test filter installed 6
8.5 Stability of wet environment 6
8.6 Water fog concentration and sedimentation check 7
8.7 Water tightness test with no test filter installed 7
8.8 Water droplet size distributions 7
8.9 Summary of qualification requirements 7
8.10 Apparatus maintenance 8

9 Test procedure 8
9.1 Preparation of filter to be tested 8
9.2 Initial pressure drop 9
9.3 Test procedure for water endurance performance of filter elements 9
9.3.1 General 9
9.3.2 Wet equilibrium pre-treatment 9
9.3.3 Water fog test 10
9.4 Water penetration ratio 10

10 Test report 10
10.1 General 10
10.2 Interpretation of test reports 11
10.3 Summaries of test results 11
10.4 Water fog mass and pressure drop 12
10.5 Marking 12

Annex A (informative) Resistance to air flow and water generation mass calculation 13

Annex B (informative) Water endurance test for vertical installed air filters 14

Annex C (informative) Water endurance of air filter elements without wet equilibrium pre-treatment 17

Annex D (normative) Water penetration ratio test 19

Annex E (informative) Leak detection and first water droplet detection procedure 20

Annex F (informative) Examples of completed test reports 23

Bibliography 31