

ISO 29461-2:2022-08 (E)

Air intake filter systems for rotary machinery - Test methods - Part 2: Filter element endurance test in fog and mist environments

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols and abbreviated terms	3
5	General requirements	4
6	Test conditions	4
6.1	Test air	4
6.2	Test water	4
7	Test rig and equipment	5
7.1	Test rig	5
7.2	Water spray device	6
7.3	Humidifying device	6
7.4	Water collecting groove	6
8	Qualification of test rig and apparatus	6
8.1	Pressure system test	6
8.2	Air leakage test	6
8.3	Air velocity uniformity in the test duct	6
8.4	Pressure drop of test duct with no test filter installed	6
8.5	Stability of wet environment	6
8.6	Water fog concentration and sedimentation check	7
8.7	Water tightness test with no test filter installed	7
8.8	Water droplet size distributions	7
8.9	Summary of qualification requirements	7
8.10	Apparatus maintenance	8
9	Test procedure	8
9.1	Preparation of filter to be tested	8
9.2	Initial pressure drop	9
9.3	Test procedure for water endurance performance of filter elements	9
9.3.1	General	9
9.3.2	Wet equilibrium pre-treatment	9
9.3.3	Water fog test	10
9.4	Water penetration ratio	10
10	Test report	10
10.1	General	10
10.2	Interpretation of test reports	11
10.3	Summaries of test results	11
10.4	Water fog mass and pressure drop	12
10.5	Marking	12

Annex A (informative) Resistance to air flow and water generation mass calculation	13
Annex B (informative) Water endurance test for vertical installed air filters	14
Annex C (informative) Water endurance of air filter elements without wet equilibrium pre-treatment	17
Annex D (normative) Water penetration ratio test	19
Annex E (informative) Leak detection and first water droplet detection procedure	20
Annex F (informative) Examples of completed test reports	23
Bibliography	31