

DIN EN 1300:2024-01 (E)

Secure storage units - Classification for high security locks according to their resistance to unauthorized opening

| Contents | | Page |
|-------------------------|---|-------------|
| European foreword | | 4 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 7 |
| 4 | Classification | 13 |
| 5 | Requirements | 13 |
| 5.1 | General requirements | 13 |
| 5.1.1 | General | 13 |
| 5.1.2 | Requirements for all classes | 13 |
| 5.1.3 | Class D HSL | 13 |
| 5.1.4 | Mechanical key operated HSL | 14 |
| 5.1.5 | Lift heights for mechanical key locks | 14 |
| 5.1.6 | Electronic HSL | 14 |
| 5.1.7 | Electronic tokens | 16 |
| 5.1.8 | Firmware updates | 17 |
| 5.2 | Security requirements | 17 |
| 5.2.1 | Usable codes | 17 |
| 5.2.2 | HSL having over ride feature | 17 |
| 5.2.3 | Manipulation resistance | 17 |
| 5.2.4 | Destructive burglary resistance | 18 |
| 5.2.5 | Spying resistance | 18 |
| 5.2.6 | Electrical and electromagnetic resistance | 18 |
| 5.2.7 | Physical environmental resistance | 19 |
| 5.2.8 | Temperature resistance | 19 |
| 5.3 | Reliability requirements | 21 |
| 6 | Technical documentation | 22 |
| 7 | Test specimens | 22 |
| 8 | Test methods | 23 |
| 8.1 | General | 23 |
| 8.1.1 | General | 23 |
| 8.1.2 | Evaluation by inspection | 23 |
| 8.1.3 | Test procedure | 23 |
| 8.2 | Security tests | 25 |
| 8.2.1 | Usable codes | 25 |
| 8.2.2 | Manipulation resistance | 25 |
| 8.2.3 | Destructive burglary resistance | 28 |
| 8.2.4 | Spying resistance | 28 |
| 8.2.5 | Electrical and electromagnetic resistance | 29 |
| 8.2.6 | Physical environmental resistance | 30 |
| 8.2.7 | Temperature resistance | 32 |
| 8.3 | Reliability testing | 32 |
| 8.3.1 | Cycling | 32 |
| 8.3.2 | Code changes | 33 |

| | | |
|--|--|----|
| 8.3.3 | Dynamic code input of mechanical combination HSL | 33 |
| 9 | Test report | 34 |
| 10 | Marking | 34 |
| Annex A (normative) Parameters for installation and operation instructions | | 35 |
| Annex B (normative) Determination of manipulation resistance due to the design requirement | | 37 |
| B.4.2 | Sniffing the code via the data cable connection | 44 |
| B.4.3 | Sniffing the code via key logger | 45 |
| B.4.4 | Replay attack via the cable connection | 46 |
| B.4.5 | Brute force attack | 47 |
| B.4.6 | Side channel attacks | 48 |
| B.4.7 | Lock spiking | 49 |
| B.4.8 | Mechanical bypassing | 49 |
| B.4.9 | Optical code spying | 49 |
| Annex C (informative) Example of manufacturer's declaration | | 50 |
| Annex D (informative) Typical locking device dimensions | | 52 |
| Annex E (normative) Determination of burglary resistance due to the design requirement | | 53 |
| Annex F (informative) Example of firmware declaration | | 54 |
| Annex G (informative) A-deviations | | 55 |
| 58 | Bibliography | |