

ISO 11500:2022-12 (E)

Hydraulic fluid power - Determination of the particulate contamination level of a liquid sample by automatic particle counting using the light-extinction principle

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Materials and equipment	2
5	Diluent liquid	3
6	Pre-test requirements and procedures	4
6.1	Precautions	4
6.1.1	Chemicals	4
6.1.2	Electrical interference	4
6.1.3	Use of magnetic stirrer	4
6.1.4	Relative humidity	4
6.1.5	Sample storage	4
6.2	Glassware cleaning procedure	4
6.3	APC calibration procedure	5
6.4	APC operation	5
6.5	Sample inspection and preparation before counting	5
6.5.1	Outline	5
6.5.2	Initial preparation and inspection	5
6.5.3	Preparation of sample of excessive volume	6
6.5.4	Determination of presence of water	7
6.6	Determination of need for sample dilution	7
7	Procedure for determining the particulate contamination level by automatic counting	7
7.1	Outline	7
7.2	Sample dilution	8
7.2.1	Use of sample dilution	8
7.2.2	Precautions	9
7.2.3	Volumetric dilution method	9
7.2.4	Mass dilution method	10
7.3	Analysis procedure	10
8	Test report	12
9	Identification statement (reference to this document)	13
Annex A (normative) Procedure for performing a statistical check of an automatic particle counter		14
Annex B (informative) Acceptable diluents		15
Annex C (informative) Method for pre-cleaning diluent and method for incorporating additives into the diluent to eliminate the influence of static electricity on particle counts		16

Annex D (informative) Reporting particulate contamination level in a hydraulic liquid sample as determined by automatic counting	18
Bibliography	20