

# ISO 4548-14:2023-03 (E)

## Methods of test for full-flow lubricating oil filters for internal combustion engines - Part 14: Hydraulic pulse durability for composite filter housings

---

| <b>Contents</b>   |   | <b>Page</b> |
|---|---|-------------|
| Foreword .....  |   | iv          |
| Introduction .....  |   | v           |
| 1   | <b>Scope .....</b>                                    | <b>1</b>    |
| 2   | <b>Normative references .....</b>                     | <b>1</b>    |
| 3   | <b>Terms, definitions and graphical symbols .....</b> | <b>1</b>    |
| 3.1   | <b>Terms and definitions .....</b>                    | <b>1</b>    |
| 3.2   | <b>Graphical symbols .....</b>                        | <b>1</b>    |
| 4   | <b>Operational characteristics to be tested .....</b> | <b>1</b>    |
| 5   | <b>Test equipment .....</b>                           | <b>2</b>    |
| 6   | <b>Test liquid .....</b>                              | <b>2</b>    |
| 7   | <b>Test temperature .....</b>                         | <b>2</b>    |
| 8   | <b>Accuracy .....</b>                                 | <b>2</b>    |
| 9   | <b>Hydraulic pulse durability test .....</b>          | <b>2</b>    |
| 10  | <b>Test report .....</b>                              | <b>5</b>    |
| <b>Annex A (informative) Values to be used for tests if no agreement is reached with the<br/>manufacturer .....</b> |   | <b>6</b>    |
| <b>Bibliography .....</b>   |   | <b>7</b>    |