

# DIN EN 17038-4:2024-04 (E)

## Pumps - Methods of qualification of the Energy Efficiency Index for rotodynamic pump units - Part 4 : Testing and calculation of energy efficiency index (EEI) of submersible multistage pump units

### Contents

Page

European foreword .....	4
Introduction .....	5
1 Scope.....	6
2 Normative references.....	6
3 Terms and definitions.....	7
4 Symbols and abbreviations .....	10
5 General conditions for the operation of submersible multistage pump units .....	12
6 Reference flow-time profiles and reference pressure control curve.....	12
6.1 General.....	12
6.2 Reference flow-time profiles .....	13
6.3 Reference pressure control curves .....	14
7 Determination of average electric power input $P_{1,\text{avg}}$ by test.....	14
7.1 General.....	14
7.1.1 Introduction.....	14
7.1.2 Test conditions .....	14
7.1.3 Measuring instrumentation .....	15
7.1.4 Uncertainties of measured quantities.....	16
7.2 Measurement procedure.....	16
7.2.1 Measurement steps .....	16
7.2.2 Determination of $Q_{100} \%$ and $H_{100} \%$ .....	16
7.2.3 Determination of reference load points .....	16
7.2.4 Adjustment tolerances.....	17
7.2.5 Corrections for deviations in flow and head .....	17
7.3 Calculation of $P_{1,\text{avg}}$ .....	17
8 Determination of average electric power input $P_{1,\text{avg}}$ by the means of a Semi-Analytical Model.....	18
8.1 General.....	18
8.2 The semi-analytical model of submersible rotodynamic pumps .....	18
8.3 Pump units in fixed speed operation .....	19
8.3.1 General.....	19
8.3.2 Model of the electric motor .....	20
8.3.3 Interaction of pump and motor .....	20
8.3.4 Determination of $Q_{100} \%$ and $H_{100} \%$ .....	20
8.3.5 Determination of the $P_{1,\text{avg},c}$ -value .....	21
8.4 Pump units with a Power Drive System (PDS) .....	22
8.4.1 General.....	22
8.4.2 Model of the Power Drive System (PDS) .....	24
8.4.3 Interaction of pump and PDS.....	26
8.4.4 Determination of $Q_{100} \%$ and $H_{100} \%$ .....	27
8.4.5 Determination of $P_{1,\text{avg}}$ for pump units with PDS .....	27

<b>9</b>	<b>Determination of reference electric power input <math>P_{1,\text{ref}}</math></b>	<b>28</b>
<b>10</b>	<b>Calculation of Energy Efficiency Index (EEI)</b>	<b>31</b>
<b>Annex A (informative) Generation of input data for the models of components of a submersible multistage pump unit</b>		<b>32</b>
<b>A.1</b>	<b>General</b>	<b>32</b>
<b>A.2</b>	<b>Input data for the model of a submersible rotodynamic pump</b>	<b>32</b>
<b>A.3</b>	<b>Input data for the model of a submersible grid fed motor</b>	<b>33</b>
<b>A.4</b>	<b>Input data for the model of a PDS consisting of submersible motor and CDM</b>	<b>33</b>
<b>Annex B (informative) Experimental Determination of thrust bearing friction losses</b>		<b>35</b>
<b>Annex C (informative) Determination of EEI values using data for RCDMs</b>		<b>36</b>
<b>Bibliography</b>		<b>37</b>