

ISO 23316-5:2023-10 (E)

Tractors and machinery for agriculture and forestry - Electrical high-power interface 700 V DC / 480 V AC - Part 5: DC operation mode

Contents		Page
Foreword		iv
Introduction		v
1 Scope		1
2 Normative references		1
3 Terms, definitions and symbols		1
3.1 Terms and definitions		1
3.2 Symbols		2
4 System overview		3
4.1 General		3
4.2 Operation with single CS		4
4.3 Operation with MCS		5
5 DC specification		8
5.1 Voltage form and quality		8
5.1.1 System voltage: values and ranges		8
5.1.2 Voltage ripple		8
5.1.3 Continuous DC current		9
5.1.4 Peak current		9
5.1.5 Current specific communication parameters		10
5.1.6 Voltage dips and recovery time		10
5.1.7 Overvoltage protection		10
5.1.8 Overcurrent protection		10
5.1.9 System inductance		12
5.1.10 DC link capacitance		12
5.1.11 Y-capacitors, parasitic capacitances		13
5.1.12 DC Link pre-charging		13
5.2 DC link discharging procedure		15
5.2.1 General		15
5.2.2 Connection of MCS		15
5.3 Compatibility criteria for PS, HPI and load		16
5.3.1 Block diagram		16
5.3.2 Value ranges for system components:		17
5.3.3 Limitations on ripple current		17
5.3.4 Test methods		18
5.3.5 Ripple current in case of MCS		19
5.3.6 Limited operation of source-load(s) combinations with respect to ripple currents		20
5.3.7 Energy feedback		20
5.3.8 Functional requirements — Energy feedback over time		21
5.4 Overload protection		21
Annex A (informative) Estimation methods for DC link film capacitors		22
Annex B (informative) Technical details		24
Bibliography		36