

ISO 6953-1:2024-01 (E)

Pneumatic fluid power - Compressed air pressure regulators and filter-regulators - Part 1: Main characteristics to include in supplier's literature and product-marking requirements

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 2 |
| 4 | Technical requirements | 3 |
| 4.1 | General | 3 |
| 4.2 | General characteristics | 3 |
| 4.2.1 | General dimensions | 3 |
| 4.2.2 | Port forms | 4 |
| 4.2.3 | Rated pressure | 4 |
| 4.2.4 | Range of operating temperatures | 4 |
| 4.3 | Particular requirements | 4 |
| 4.3.1 | General | 4 |
| 4.3.2 | Adjustable pressure ranges (outlet regulated pressure) | 4 |
| 4.3.3 | Flow rate-pressure characteristics | 5 |
| 4.3.4 | Pressure regulation characteristic | 6 |
| 4.3.5 | Pilot pressure/regulated pressure characteristics | 6 |
| 4.3.6 | Repeatability | 8 |
| 4.3.7 | Output resolution in the case of manual air pressure | 8 |
| 4.3.8 | Resolution in the case of pressure-pilot air pressure regulator | 8 |
| 4.3.9 | Sensitivity for manual and pressure-pilot air pressure regulator | 8 |
| 4.3.10 | Maximum air consumption at null forward flow rate or relief flow rate for pilot- operated regulator with air bleed | 8 |
| 4.3.11 | Useful retention capacity of the reservoir | 8 |
| 4.3.12 | Filter-regulator draining devices | 9 |
| 4.3.13 | Materials of construction | 9 |
| 5 | Operation and maintenance | 9 |
| 6 | Marking | 9 |
| 7 | Identification statement -- Reference to ISO 6953-1 (this document) | 9 |
| Bibliography | | 11 |