

ISO 16122-4:2024-12 (E)

Agricultural and forestry machinery - Inspection of sprayers in use - Part 4: Fixed and semi-mobile sprayers

Contents

	Page
Foreword.....	v
Introduction.....	vii
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	1
4 Requirements and method of verification.....	1
4.1 General.....	1
4.2 Leaks and dripping.....	2
4.2.1 Static leaks.....	2
4.2.2 Dynamic leaks.....	2
4.2.3 Spraying and dripping on parts.....	2
4.3 Pump(s).....	2
4.3.1 Capacity.....	2
4.3.2 Pulsations.....	3
4.3.3 Air chamber.....	3
4.4 Spray mix agitation.....	3
4.4.1 Hydraulic.....	3
4.4.2 Mechanical.....	3
4.5 Spray tank(s).....	4
4.5.1 Lid.....	4
4.5.2 Tank filling strainer(s).....	4
4.5.3 Pressure compensation.....	4
4.5.4 Tank content indicator(s).....	4
4.5.5 Tank emptying.....	4
4.5.6 Tank filling.....	4
4.5.7 Induction hopper.....	4
4.5.8 Cleaning device for plant protection product containers.....	5
4.5.9 Cleaning equipment.....	5
4.6 Measuring systems, controls and regulation systems.....	5
4.6.1 General.....	5
4.6.2 Pressure indicator for spray liquid.....	5
4.6.3 Other measuring devices.....	6
4.6.4 Pressure adjusting devices.....	6
4.6.5 Direct injection systems.....	6
4.7 Lines (pipes and hoses).....	7
4.7.1 Lines.....	7
4.8 Filters.....	7
4.8.1 Filter presence.....	7
4.8.2 Isolating device.....	7
4.8.3 Filter insert changeability.....	7
4.9 Application unit.....	7
4.9.1 Dripping.....	7
4.9.2 Horizontal spray booms.....	7
4.9.3 Vertical spray boom.....	9
4.9.4 Spray guns and lances.....	10
4.10 Blower.....	10
4.10.1 Condition.....	10
4.10.2 Adjustability.....	10
4.11 Distribution.....	10

4.11.1	Uniformity of spray jet.....	10
4.11.2	Nozzle output	11
4.11.3	Spray distribution measurement on a patternator (optional)	11
4.11.4	Optional vertical distribution information	11
4.12	Autonomous application units.....	11
4.12.1	Drive system	11
4.12.2	Travel speed spray robots.....	12
4.13	Cleaning equipment.....	12
5	Test methods.....	12
5.1	Test facilities and equipment.....	12
5.1.1	General.....	12
5.1.2	Test facilities	12
5.2	Spray agitation pumps.....	12
5.2.1	Pump capacity test.....	12
5.2.2	Pump pulsations.....	14
5.3	Sprayer's pressure indicators.....	14
5.3.1	Specification of pressure indicators used for verification.....	14
5.3.2	Verification method of the sprayer pressure indicator	14
5.4	Flow meters for controlling the volume/area rate.....	15
5.4.1	General.....	15
5.4.2	Operating procedure No. 1: Verification by nozzle flow rate measurement.....	15
5.4.3	Operating Procedure No. 2: Verification by installing a calibrated flow meter in the circuit of the sprayer.....	15
5.5	System for controlling forward speed.....	15
5.6	Uniformity of the transverse volume distribution with a horizontal patternator.....	15
5.6.1	Specification of the horizontal patternators used for verification.....	15
5.6.2	Calculation of coefficient of variation (C_V).....	16
5.6.3	Verification method of the uniformity of the transverse distribution	16
5.6.4	Verification method of spray gun/lance flow rate.....	16
5.7	Flow rate of the spray nozzles.....	16
5.7.1	General.....	16
5.7.2	Measurement with nozzles fitted on the sprayer.....	17
5.7.3	Measurement with nozzles removed from the sprayer.....	17
5.8	Pressure drop.....	17
5.9	Pressure variation when the sections are closed.....	17
5.10	Pressure variation when the spray is switched off	17
5.11	Accuracy of direct injection systems.....	17
5.12	Pressure distribution	18
	Bibliography.....	19