

ISO 16625:2025-02 (E)

Cranes and hoists - Selection of wire ropes, drums and sheaves

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms, definitions and symbols	2
3.1	Terms and definitions	2
3.2	Symbols	2
4	Running ropes and stationary ropes	5
4.1	General	5
4.2	Discard criteria	5
4.3	Rope and rope terminations	6
5	Proof of competence of running ropes	6
5.1	Proof of static strength	6
5.1.1	General	6
5.1.2	Vertical hoisting of loads	6
5.1.3	General rope drives	12
5.1.4	Limit design rope force	15
5.2	Proof of fatigue strength	16
5.2.1	General	16
5.2.2	Design rope force	19
5.2.3	Limit design rope force	22
5.3	Proof of competence for multilayer spooling	27
5.3.1	General	27
5.3.2	Vertical hoisting of loads	28
5.3.3	General rope drive	28
5.3.4	Limit design rope force	29
6	Proof of competence of stationary ropes	30
6.1	Proof of static strength	30
6.1.1	General	30
6.1.2	Limit design rope force	30
6.2	Proof of fatigue strength	31
6.2.1	General	31
6.2.2	Limit design rope force	31
Annex A (normative)	Number of relevant bending cycles	33
Annex B (informative)	Determination of the maximum tensile force in the ropes of multi-rope grabs (holding and closing)	45
Annex C (informative)	Comparison of minimum design factor according to ISO 16625:2013 and safety level according current version	46
Annex D (informative)	Selection of a rope by minimum design factor Z_p	50
Annex E (informative)	Assumed number of hoist ropes l_r during the design life of a crane	52
Annex F (informative)	Other rope-related design and rope selection aspects	54
Bibliography		66