ISO 24477:2025-03 (E)

Vacuum technology - Vacuum gauges - Specifications, calibration and measurement uncertainties for spinning rotor gauges

Contents

Page

Foreword ... **iv**

Introduction ... **v**

1 Scope ... **1**

2 Normative references ... **1**

3 Terms and definitions ... **1**
3.1 Terms related to components ... 2
3.2 Terms related to physical parameters ... 2

4 Symbols and abbreviated terms ... **4**

5 Principle of a spinning rotor gauge ... **4**

6 Specifications for spinning rotor gauge ... **5**
6.1 Diameter and density of rotor ... 5
6.2 Materials of rotor and thimble ... 5
6.3 Connecting flange of thimble ... 6
6.4 Leak rate of thimble with flange ... 6
6.5 Suspension head positioning ... 6
6.6 Limits of rotor frequency ... 6
6.7 Warm-up period ... 6
6.8 Baking temperature ... 6
6.9 Measurement range ... 6
6.10 Sampling time ... 6
6.11 Internal volume ... 6
6.12 Interface and pin connections of controller ... 6
6.13 Dimensions and weights of suspension head and controller ... 6
6.14 Display and signal output ... 6
6.15 Nominal operating (environment) conditions ... 7
6.16 Storage and transportation conditions ... 7
6.17 Input power and electrical requirements ... 7
6.18 Number of display digits ... 7

7 Additional (optional) specifications for spinning rotor gauge ... **7**
7.1 Long-term instability ... 7
7.2 Expected measurement uncertainty ... 7
7.3 Compatibility between a suspension head and a rotor ... 7
7.4 Inspection record and calibration certificate ... 7
7.5 Allowed vibration level ... 7
7.6 Cable length ... 8
7.7 Photograph ... 8

8 Calibration ... **8**
8.1 Parameters to be calibrated ... 8
8.2 Calibration procedures ... 8
8.2.1 General ... 8
8.2.2 Calibration method A for $\sigma_{eff,0}$ ... 9
8.2.3 Calibration method B for $\sigma_{eff,0}$ ... 9
8.3 Calibration uncertainty ... 10
8.4 Calibration certificate ... 10

9 Measurement uncertainty at use ... **10**

Bibliography ... **11**