

# ISO 8426-1:2025-08 (E)

## Hydraulic fluid power - Determination of derived displacement of positive displacement pumps and motors - Part 1: Two-step Toet method

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
1	<b>Scope .....</b>	<b>1</b>
2	<b>Normative references .....</b>	<b>1</b>
3	<b>Terms and definitions .....</b>	<b>1</b>
4	<b>Symbols and units .....</b>	<b>1</b>
5	<b>Test procedure .....</b>	<b>2</b>
5.1	<b>General requirements .....</b>	<b>2</b>
5.2	<b>Number of steady-state shaft speeds and differential pressures .....</b>	<b>3</b>
5.3	<b>Variable displacement unit .....</b>	<b>3</b>
5.4	<b>Reverse flow unit .....</b>	<b>3</b>
5.5	<b>Unit used as pump or motor .....</b>	<b>3</b>
6	<b>Calculation of derived displacement .....</b>	<b>4</b>
6.1	<b>General .....</b>	<b>4</b>
6.2	<b>The two-step Toet method .....</b>	<b>4</b>
7	<b>Test report .....</b>	<b>5</b>
<b>Annex A (informative) Test report examples .....</b>		<b>7</b>
<b>Annex B (informative) Formulae for fitting a line .....</b>		<b>15</b>
<b>Bibliography .....</b>		<b>16</b>