DIN EN ISO 16122-4:2026-05 (E)

Agricultural and forestry machines - Inspection of sprayers in use - Part 4: Fixed and semi-mobile sprayers (ISO 16122-4:2024)

Contents

Page

Foreword ..... **v**

Introduction ..... **vii**

1 Scope **1**

2 Normative references **1**

3 Terms and definitions **1**

4 Requirements and method of verification **1**

4.1 General 1
4.2 Leaks and dripping 2
4.2.1 Static leaks 2
4.2.2 Dynamic leaks 2
4.2.3 Spraying and dripping on parts 2
4.3 Pump(s) 2
4.3.1 Capacity 2
4.3.2 Pulsations 3
4.3.3 Air chamber 3
4.4 Spray mix agitation 3
4.4.1 Hydraulic 3
4.4.2 Mechanical 3
4.5 Spray tank(s) 4
4.5.1 Lid 4
4.5.2 Tank filling strainer(s) 4
4.5.3 Pressure compensation 4
4.5.4 Tank content indicator(s) 4
4.5.5 Tank emptying 4
4.5.6 Tank filling 4
4.5.7 Induction hopper 4
4.5.8 Cleaning device for plant protection product containers 5
4.5.9 Cleaning equipment 5
4.6 Measuring systems, controls and regulation systems 5
4.6.1 General 5
4.6.2 Pressure indicator for spray liquid 5
4.6.3 Other measuring devices 6
4.6.4 Pressure adjusting devices 6
4.6.5 Direct injection systems 6
4.7 Lines (pipes and hoses) 7
4.7.1 Lines 7
4.8 Filters 7
4.8.1 Filter presence 7
4.8.2 Isolating device 7
4.8.3 Filter insert changeability 7
4.9 Application unit 7
4.9.1 Dripping 7
4.9.2 Horizontal spray booms 7
4.9.3 Vertical spray boom 9
4.9.4 Spray guns and lances 10
4.10 Blower 10
4.10.1 Condition 10
4.10.2 Adjustability 10
4.11 Distribution 10

4.11.1 Uniformity of spray jet 10
4.11.2 Nozzle output 11
4.11.3 Spray distribution measurement on a patternator (optional) 11
4.11.4 Optional vertical distribution information 11
4.12 Autonomous application units 11
4.12.1 Drive system 11
4.12.2 Travel speed spray robots 12
4.13 Cleaning equipment 12
5 Test methods 12
5.1 Test facilities and equipment 12
5.1.1 General 12
5.1.2 Test facilities 12
5.2 Spray agitation pumps 12
5.2.1 Pump capacity test 12
5.2.2 Pump pulsations 14
5.3 Sprayer´s pressure indicators 14
5.3.1 Specification of pressure indicators used for verification 14
5.3.2 Verification method of the sprayer pressure indicator 14
5.4 Flow meters for controlling the volume/area rate 15
5.4.1 General 15
5.4.2 Operating procedure No. 1: Verification by nozzle flow rate measurement 15
5.4.3 Operating Procedure No. 2: Verification by installing a calibrated flow meter in the circuit of the sprayer 15
5.5 System for controlling forward speed 15
5.6 Uniformity of the transverse volume distribution with a horizontal patternator 15
5.6.1 Specification of the horizontal patternators used for verification 15
5.6.2 Calculation of coefficient of variation (C_V) 16
5.6.3 Verification method of the uniformity of the transverse distribution 16
5.6.4 Verification method of spray gun/lance flow rate 16
5.7 Flow rate of the spray nozzles 16
5.7.1 General 16
5.7.2 Measurement with nozzles fitted on the sprayer 17
5.7.3 Measurement with nozzles removed from the sprayer 17
5.8 Pressure drop 17
5.9 Pressure variation when the sections are closed 17
5.10 Pressure variation when the spray is switched off 17
5.11 Accuracy of direct injection systems 17
5.12 Pressure distribution 18
Bibliography 19