

ISO 20145:2026-02 (E)

Pneumatic fluid power - Test methods for measuring acoustic emission pressure levels of exhaust silencers

| Contents | | Page |
|------------------------------|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Symbols and units | 3 |
| 5 | Test set-up | 3 |
| 5.1 | Test bench | 3 |
| 5.2 | Pneumatic pressure measurement | 3 |
| 5.3 | Flow measurement | 3 |
| 5.4 | Sound pressure measurement | 3 |
| 5.4.1 | General | 3 |
| 5.4.2 | Measurement at one position | 4 |
| 5.4.3 | Measurement at three positions | 4 |
| 5.5 | Acoustic instrumentation | 5 |
| 6 | Test procedure | 6 |
| 6.1 | Characterization and validation of the test facilities | 6 |
| 6.2 | Quantities to be measured | 6 |
| 6.2.1 | Basic quantities to be measured | 6 |
| 6.2.2 | Acquisition parameters of basic quantities — Steady-state mode | 6 |
| 6.2.3 | Acquisition parameters of basic quantities — Discharge mode | 6 |
| 6.3 | Measurements | 7 |
| 6.3.1 | General | 7 |
| 6.3.2 | Specimens tested | 7 |
| 6.3.3 | Specific cases | 7 |
| 6.3.4 | Ambient conditions during measurement | 8 |
| 6.4 | The acoustic quantity to be determined | 8 |
| 6.5 | Calculation of background noise correction K_{1A} | 8 |
| 6.5.1 | General | 8 |
| 6.5.2 | Case of measurement in steady-state mode | 9 |
| 6.5.3 | Case of measurement in discharge mode | 9 |
| 6.6 | Uncertainty on measurement | 10 |
| 7 | Presentation of test results | 10 |
| 7.1 | Information to be written in the test report | 10 |
| 7.2 | Information to be declared | 11 |
| 8 | Identification statement | 11 |
| Annex A (informative) | Calculation of environmental correction K_{2A} | 12 |
| Annex B (informative) | Example of the acoustic correction of industrial facilities | 14 |
| Annex C (informative) | Example of reports | 18 |
| Annex D (informative) | Uncertainties | 20 |
| Annex E (informative) | Sound attenuation effect of silencers | 23 |
| Bibliography | | 34 |