

# ISO 18646-5:2026-07 (E)

## Robotics - Performance criteria and related test methods for service robots - Part 5: Locomotion for legged robots

---

### Contents

Page

|                                     |    |
|-------------------------------------|----|
| Foreword .....                      | v  |
| Introduction .....                  | vi |
| 1 Scope .....                       | 1  |
| 2 Normative references .....        | 1  |
| 3 Terms and definitions .....       | 1  |
| 4 Test conditions .....             | 2  |
| 4.1 General .....                   | 2  |
| 4.2 Environmental conditions .....  | 2  |
| 4.3 Travel surface conditions ..... | 2  |
| 4.4 Operating conditions .....      | 3  |
| 5 Rated speed .....                 | 3  |
| 5.1 Purpose .....                   | 3  |
| 5.2 Test facility .....             | 3  |
| 5.3 Test procedure .....            | 3  |
| 5.4 Test result .....               | 4  |
| 6 Stopping distance .....           | 4  |
| 6.1 Purpose .....                   | 4  |
| 6.2 Test facility .....             | 4  |
| 6.3 Test procedure .....            | 5  |
| 6.4 Test result .....               | 5  |
| 7 Maximum climbing height .....     | 5  |
| 7.1 Purpose .....                   | 5  |
| 7.2 Test facility .....             | 6  |
| 7.3 Test procedure .....            | 6  |
| 7.4 Test result .....               | 6  |
| 8 Capacity to climb stairs .....    | 6  |
| 8.1 Purpose .....                   | 6  |
| 8.2 Test facility .....             | 7  |
| 8.3 Test procedure .....            | 7  |
| 8.4 Test result .....               | 8  |
| 9 Maximum slope angle .....         | 8  |
| 9.1 Purpose .....                   | 8  |
| 9.2 Test facility .....             | 8  |
| 9.3 Test procedure .....            | 9  |
| 9.4 Test result .....               | 9  |
| 10 Dragging force .....             | 10 |
| 10.1 Purpose .....                  | 10 |
| 10.2 Test facility .....            | 10 |
| 10.3 Test procedure .....           | 11 |
| 10.4 Test result .....              | 11 |

|                            |                                          |           |
|----------------------------|------------------------------------------|-----------|
| <b>11</b>                  | <b>Crossing capacity .....</b>           | <b>11</b> |
| <b>11.1</b>                | <b>Purpose .....</b>                     | <b>11</b> |
| <b>11.2</b>                | <b>Test facility .....</b>               | <b>11</b> |
| <b>11.3</b>                | <b>Test procedure .....</b>              | <b>13</b> |
| <b>11.4</b>                | <b>Test result .....</b>                 | <b>13</b> |
| <b>12</b>                  | <b>Minimum pass-through height .....</b> | <b>13</b> |
| <b>12.1</b>                | <b>Purpose .....</b>                     | <b>13</b> |
| <b>12.2</b>                | <b>Test facility .....</b>               | <b>13</b> |
| <b>12.3</b>                | <b>Test procedure .....</b>              | <b>14</b> |
| <b>12.4</b>                | <b>Test result .....</b>                 | <b>14</b> |
| <b>13</b>                  | <b>Minimum travel width .....</b>        | <b>14</b> |
| <b>13.1</b>                | <b>Purpose .....</b>                     | <b>14</b> |
| <b>13.2</b>                | <b>Test facility .....</b>               | <b>14</b> |
| <b>13.3</b>                | <b>Test procedure .....</b>              | <b>15</b> |
| <b>13.4</b>                | <b>Test result .....</b>                 | <b>16</b> |
| <b>Annex A (normative)</b> | <b>Test report .....</b>                 | <b>17</b> |
| <b>Bibliography .....</b>  |                                          | <b>18</b> |