

ISO 10303-511:2001-04 (E)

Industrial automation systems and integration - Product data representation and exchange - Part 511: Application interpreted construct: Topologically bounded surface

Contents		Page
1	Scope	1
2	Normative references	2
3	Terms, definitions and abbreviations	2
3.4	Other definitions	3
3.5	Abbreviations	4
4	EXPRESS short listing	4
4.1	Fundamental concepts and assumptions	6
4.2	aic topologically bounded surface schema entity definition: advanced face	8
Annex A (normative) Short names of entities		12
Annex B (normative) Information object registration		13
B.1	Document identification	13
B.2	Schema identification	13
Annex C (informative) Computer-interpretable listings		14
Annex D (informative) EXPRESS-G diagrams		15
Index		24
Figures Figure D.1 aic topologically bounded surface EXPRESS-G diagram page 1 of 8		16
Figure D.2 aic topologically bounded surface EXPRESS-G diagram page 2 of 8		17
Figure D.3 aic topologically bounded surface EXPRESS-G diagram page 3 of 8		18
Figure D.4 aic topologically bounded surface EXPRESS-G diagram page 4 of 8		19
Figure D.5 aic topologically bounded surface EXPRESS-G diagram page 5 of 8		20
Figure D.6 aic topologically bounded surface EXPRESS-G diagram page 6 of 8		21
Figure D.7 aic topologically bounded surface EXPRESS-G diagram page 7 of 8		22
Figure D.8 aic topologically bounded surface EXPRESS-G diagram page 8 of 8		23
Tables Table A.1 Short names of entities		12