

ISO/TR 14179-1:2001-07 (E)

Gears - Thermal capacity - Part 1: Rating gear drives with thermal equilibrium at 95 °C sump temperature

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Symbols and units, term and definition	1
3	Rating criteria	4
4	Service conditions	5
4.1	Intermittent service	5
4.2	Adverse conditions	5
4.3	Favourable conditions	5
4.4	Auxiliary cooling	5
5	Methods for determining the thermal rating	6
6	Method A -- Test	6
7	Method B -- Calculations for determining the thermal power rating, PT	6
7.1	Basis	6
7.2	Heat generation	7
7.3	Bearing power loss, PB	7
7.4	Mesh power loss, PM, spur and helical gears	11
7.5	Mesh power loss, PM, bevel gears	14
7.6	Mesh power loss, PM, cylindrical worm gears	14
7.7	Mesh power loss, PM, double enveloping worm gears	14
7.8	Oil seal power loss, PS	14
7.9	Gear windage and churning power loss, PW	15
7.10	Bearing windage and churning power loss, PWB	16
7.11	Oil pump power loss, PP	19
7.12	Heat dissipation, PQ	20
8	Modifications for non-standard operating conditions	21
Annex A (informative) Bevel gear mesh and gear windage power losses		24
Annex B (informative) Worm gear mesh power losses		28
Bibliography		30