

# ISO 4548-4:1997-12 (E)

## Methods of test for full-flow lubricating oil filters for internal combustion engines - Part 4: Initial particle retention efficiency, life and cumulative efficiency (gravimetric method)

---

<b>Contents</b>	<b>Page</b>
<b>Section 1: General</b> .....	<b>1</b>
1.1 Scope .....	1
1.2 Normative references .....	1
1.3 Definitions .....	2
1.4 Graphical symbols .....	2
<b>Section 2: Initial particle retention efficiency</b> .....	<b>3</b>
2.1 Operational characteristics to be assessed .....	3
2.2 Test rig .....	3
2.3 Test liquids .....	4
2.4 Test contaminant .....	5
2.5 Test procedure .....	6
2.6 Test results and calculations .....	8
2.7 Report of test results for initial particle retention efficiency .....	9
<b>Section 3: Life and cumulative efficiency</b> .....	<b>11</b>
3.1 Operational characteristics to be assessed .....	11
3.2 Test rig .....	11
3.3 Periodic checks on equipment .....	12
3.4 Test liquids .....	12
3.5 Test contaminant .....	13
3.6 Test procedure .....	13
3.7 Test results and calculations .....	17
3.8 Report of test results for life and cumulative efficiency .....	18
<b>Annexes</b>	
<b>A Test parameters for initial particle retention efficiency test</b> .....	<b>19</b>
<b>B Method for determining insolubles in test liquid samples for initial particle retention efficiency</b> .....	<b>20</b>
<b>C Test parameters for life and cumulative efficiency test</b> .....	<b>24</b>
<b>D Method for determining insolubles in test liquid samples for cumulative efficiency</b> .....	<b>25</b>
<b>E Details of equipment used in the mixing of test dust and liquid slurry</b> .....	<b>28</b>
<b>F Bibliography</b> .....	<b>30</b>