ISO 10303-24:2001-12 (E)

Industrial automation systems and integration_- Product data representation and exchange_- Part_24: Implementation methods: C_language binding of standard data access interface

Contents

page

1 Scope 1

2 Normative references 1

3 Terms, definitions, and abbreviations 2
- 3.1 Terms defined in ISO 10303-1 2
- 3.2 Terms defined in ISO 10303-11 2
- 3.3 Terms defined in ISO 10303-22 3
- 3.4 Other definitions 3
- 3.5 Abbreviations 4

4 Overview of the C language late binding of SDAI 5
- 4.1 Language bindings 5
- 4.2 Conformance 5
- 4.3 Use of late binding functions 5
  - 4.3.1 Invalid parameter values 5
  - 4.3.2 Error handling 5
  - 4.3.3 Memory management 5
  - 4.3.4 The SDAI header file 6
  - 4.3.5 Macros 6
- 4.4 Naming and typographical conventions 6

5 Constants and data type definitions 7
- 5.1 Standard error codes 7
- 5.2 EXPRESS constants 7
- 5.3 EXPRESS data types 7
  - 5.3.1 Bit data type 7
  - 5.3.2 EXPRESS simple data types 8
  - 5.3.3 Enumeration data type 9
  - 5.3.4 Select data type 9
  - 5.3.5 Entity data type 10
  - 5.3.6 Aggregate data types 10
- 5.4 SDAI data types 10
  - 5.4.1 SDAI primitive data types 10
  - 5.4.2 SDAI entity data types 11
  - 5.4.3 Iterator data type 13
  - 5.4.4 Non-persistent list data type 13
  - 5.4.5 Query source data type 13
  - 5.4.6 SDAI access type data type 13
- 5.5 C late binding-specific data types 13
  - 5.5.1 Attribute data block data type 14
  - 5.5.2 Aggregate index data type 14
  - 5.5.3 Error code data type 14
  - 5.5.4 Error handler data type 14
  - 5.5.5 Transaction commit mode data type 15
  - 5.5.6 NULL identifier data type 15

6 C late binding functions of the SDAI operations 15
6.1 Environment operations 16
6.1.1 Open session 16
6.1.2 C late binding specific arithmetic operations 16
6.1.3 C late binding specific error handling operations 17
6.1.4 C late binding specific instance operations 18
6.2 Session operations 19
6.2.1 Record event 19
6.2.2 Set event recording 19
6.2.3 Close session 20
6.2.4 Open repository 20
6.2.5 Start transaction read-write or read-only access 21
6.2.6 Break transaction 22
6.2.7 End transaction access 22
6.2.8 Create non-persistent list 23
6.2.9 Delete non-persistent list 23
6.2.10 SDAI query 24
6.2.11 C late binding specific recording operations 25
6.2.12 C late binding specific attribute data block operations 26
6.3 Repository operations 29
6.3.1 Create SDAI-model 29
6.3.2 Create schema instance 30
6.3.3 Close repository 31
6.4 Schema instance operations 31
6.4.1 Delete schema instance 31
6.4.2 Rename schema instance 32
6.4.3 Add SDAI-model 33
6.4.4 Remove SDAI-model 34
6.4.5 Validate global rule 34
6.4.6 Validate uniqueness rule 35
6.4.7 Validate instance reference domain 36
6.4.8 Validate schema instance 37
6.4.9 Is validation current 38
6.4.10 Schema instance operations for convenience 39
6.5 SDAI-model operations 40
6.5.1 Delete SDAI-model 40
6.5.2 Rename SDAI-model 41
6.5.3 Start SDAI-model access 42
6.5.4 Promote SDAI-model to read-write access 42
6.5.5 End SDAI-model access 43
6.5.6 Get entity definition 44
6.5.7 Create entity instance 44
6.5.8 Undo changes 45
6.5.9 Save changes 46
6.5.10 SDAI-model operations for convenience 46
6.6 Scope operations 48
6.6.1 Add to scope 48
6.6.2 Is scope owner 49
6.6.3 Get scope 49

6.6.4 Remove from scope 50
6.6.5 Add to export list 51
6.6.6 Remove from export list 51
6.6.7 Scoped delete 52
6.6.8 Scoped copy in same SDAI-model 53
6.6.9 Scoped copy to other SDAI-model 53
6.6.10 Validate scope reference restrictions 54
6.6.11 Scope operations for convenience 55
6.7 Type operations 57
6.7.1 Get complex entity definition 57
6.7.2 Is subtype of 58
6.7.3 Is SDAI subtype of 59
6.7.4 Is domain equivalent with 59
6.7.5 Type operations for convenience 60
6.8 Entity instance operations 61
6.8.1 Get attribute 61
6.8.2 Test attribute 62
6.8.3 Find entity instance SDAI-model 63
6.8.4 Get instance type 64
6.8.5 Is instance of 64
6.8.6 Is kind of 65
6.8.7 Is SDAI kind of 66
6.8.8 Find entity instance users 67
6.8.9 Find entity instance usedin 68
6.8.10 Get attribute value bound 69
6.8.11 Find instance roles 70
6.8.12 Find instance data types 70
6.8.13 Entity instance operations for convenience 71
6.9 Application instance operations 73
6.9.1 Copy application instance in same SDAI-model 73
6.9.2 Copy application instance to other SDAI-model 74
6.9.3 Delete application instance 75
6.9.4 Put attribute 75
6.9.5 Unset attribute value 76
6.9.6 Create aggregate instance 77
6.9.7 Create aggregate instance ADB 78
6.9.8 Get persistent label 79
6.9.9 Get session identifier 80
6.9.10 Get description 80
6.9.11 Validate where rule 81
6.9.12 Validate required explicit attributes assigned 82
6.9.13 Validate inverse attributes 83
6.9.14 Validate explicit attributes references 84
6.9.15 Validate aggregates size 85
6.9.16 Validate aggregates uniqueness 85
6.9.17 Validate array not optional 86
6.9.18 Validate string width 87
6.9.19 Validate binary width 88
6.9.20 Validate real precision 89

6.9.21 Application instance operations for convenience 90
6.10 Entity instance aggregate operations 91
6.10.1 Get member count 91
6.10.2 Is member 92
6.10.3 Create iterator 93
6.10.4 Delete iterator 94
6.10.5 Beginning 94
6.10.6 Next 95
6.10.7 Get current member 95
6.10.8 Get value bound by iterator 96
6.10.9 Get lower bound 97
6.10.10 Get upper bound 98
6.11 Application instance aggregate operations 99
6.11.1 Create aggregate instance as current member 99
6.11.2 Put current member 100
6.11.3 Remove current member 100
6.12 Application instance unordered collection operations 101
6.12.1 Add unordered 101
6.12.2 Create aggregate instance unordered 102
6.12.3 Remove unordered 103
6.13 Entity instance ordered collection operations 104
6.13.1 Get by index 104
6.13.2 End 105
6.13.3 Previous 105
6.13.4 Get value bound by index 106
6.14 Application instance ordered collection operations 107
6.14.1 Put by index 107
6.14.2 Create aggregate instance by index 108
6.15 Entity instance array operations 109
6.15.1 Test by index 109
6.15.2 Test current member 109
6.15.3 Get lower index 110
6.15.4 Get upper index 111
6.16 Application instance array operations 112
6.16.1 Unset value by index 112
6.16.2 Unset value current member 112
6.16.3 Reindex array 113
6.16.4 Reset array index 114
6.17 Application instance list operations 114
6.17.1 Add before current member 114
6.17.2 Add after current member 115
6.17.3 Add by index 116
6.17.4 Create aggregate instance before current member 117
6.17.5 Create aggregate instance after current member 118
6.17.6 Add aggregate instance by index 119
6.17.7 Remove by index 120
6.18 C late binding specific SELECT TYPE operations 120
6.18.1 Put ADB type path 121
6.18.2 Get ADB type path 121

6.18.3 Validate type path 122

Annex A (normative) Information object registration 124

Annex B (informative) The C late binding header include file <sdai.h> 125

Index 135

Tables page

Table 1 - SDAI C late binding error indicators 7
Table 2 - EXPRESS built-in constants 8
Table 3 - SDAI primitive data types mapped to C late binding 11
Table 4 - SDAI entity data types mapped to C late binding 12