

ISO 6072:2002-03 (E)

Hydraulic fluid power - Compatibility between fluids and standard elastomeric materials

| Contents | | Page |
|--|---|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 2 |
| 4 | Test elastomers | 2 |
| 4.1 | General | 2 |
| 4.2 | Standard acrylonitrile-butadiene rubber (NBR 1) | 2 |
| 4.3 | Standard acrylonitrile-butadiene rubber (NBR 2) | 4 |
| 4.4 | Standard fluoroelastomer (FKM 2) (vinylidene fluoride hexafluoropropylene copolymer) | 6 |
| 4.5 | Standard ethylene propylene diene rubber (EPDM 1) | 7 |
| 4.6 | Standard hydrogenated NBR (HNBR 1) | 9 |
| 5 | Determination of elastomer compatibility index (ECI) | 10 |
| 5.1 | General | 10 |
| 5.2 | Test conditions | 11 |
| 5.3 | Determination of percentage change in volume | 12 |
| 5.4 | Determination of change in hardness | 14 |
| 5.5 | Determination of percentage change in tensile strength and elongation at break | 14 |
| 5.6 | Test report | 15 |
| 6 | Identification statement (Reference to this International Standard) | 16 |
| Annex A (informative) Information report | | 17 |
| Annex B (informative) Example of test report -- Fluid-elastomer compatibility index (ECI) | | 19 |
| Annex C (informative) Guidelines on elastomer compatibility | | 20 |