

# ISO 6162-2:2002-12 (E)

Hydraulic fluid power - Flange connectors with split or one-piece flange chamfers and metric or inch screws - Part 2: Flange connectors for use at pressures of 35 MPa (350 bar) to 40 MPa (400 bar), DN 13 to DN 51

---

<b>Contents</b>		<b>Page</b>
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>2</b>
<b>4</b>	<b>Material .....</b>	<b>2</b>
<b>5</b>	<b>General specifications .....</b>	<b>2</b>
<b>6</b>	<b>Dimensions .....</b>	<b>3</b>
<b>7</b>	<b>Tolerances .....</b>	<b>3</b>
<b>8</b>	<b>Finish .....</b>	<b>3</b>
<b>9</b>	<b>Pressure/temperature requirements .....</b>	<b>4</b>
<b>10</b>	<b>Marking .....</b>	<b>4</b>
<b>11</b>	<b>Designation of flange connections and their parts .....</b>	<b>5</b>
<b>Annexes A Equivalent SAE O-rings .....</b>		<b>16</b>
<b>B</b>	<b>Equivalent inch screw strengths .....</b>	<b>17</b>
<b>Bibliography .....</b>		<b>18</b>