

# ISO 9283:1998-04 (E)

## Manipulating industrial robots - Performance criteria and related test methods

---

<b>Contents</b>		<b>Page</b>
1	Scope .....	1
2	Normative references .....	2
3	Definitions .....	2
4	Units .....	2
5	Abbreviations and symbols .....	3
5.1	Basic abbreviations .....	3
5.2	Quantities .....	3
5.3	Indices .....	4
5.4	Other symbols .....	4
6	Performance testing conditions .....	4
6.1	Robot mounting .....	4
6.2	Conditions prior to testing .....	4
6.3	Operating and environmental conditions .....	5
6.4	Displacement measurement principles .....	5
6.5	Instrumentation .....	6
6.6	Load to the mechanical interface .....	6
6.7	Test velocities .....	8
6.8	Definitions of poses to be tested and paths to be followed .....	9
6.9	Number of cycles .....	15
6.10	Test procedure .....	15
6.1	1 Characteristics to be tested - Applications .....	16
7	Pose characteristics .....	16
7.1	General description .....	16
7.2	Pose accuracy and pose repeatability .....	17
7.3	Distance accuracy and repeatability 24 • .....	17
7.4	Position stabilization time .....	29
7.5	Position overshoot .....	30
7.6	Drift of pose characteristics .....	31
7.7	Exchangeability .....	34
8	Path characteristics .....	35
8.1	General .....	35
8.2	Path accuracy .....	36
8.3	Path repeatability .....	37
8.4	Path accuracy on reorientation .....	39
8.5	Cornering deviations .....	40
8.6	Path velocity characteristics .....	42
9	Minimum posing time .....	44
10	Static compliance .....	46
11	Application specific Performance criteria .....	46
11.1	Weaving deviations .....	46
12	Test report .....	48

**Annex**

<b>A (normative) Parameters for comparison tests .....</b>	<b>49</b>
<b>B (informative) Guide for selection of tests for typical applications .....</b>	<b>54</b>
<b>C (informative) Example of a test report .....</b>	<b>56</b>