

ISO 9283:1998-04 (E)

Manipulating industrial robots - Performance criteria and related test methods

Contents		Page
1	Scope	1
2	Normative references	2
3	Definitions	2
4	Units	2
5	Abbreviations and symbols	3
5.1	Basic abbreviations	3
5.2	Quantities	3
5.3	Indices	4
5.4	Other symbols	4
6	Performance testing conditions	4
6.1	Robot mounting	4
6.2	Conditions prior to testing	4
6.3	Operating and environmental conditions	5
6.4	Displacement measurement principles	5
6.5	Instrumentation	6
6.6	Load to the mechanical interface	6
6.7	Test velocities	8
6.8	Definitions of poses to be tested and paths to be followed	9
6.9	Number of cycles	15
6.10	Test procedure	15
6.1	1 Characteristics to be tested - Applications	16
7	Pose characteristics	16
7.1	General description	16
7.2	Pose accuracy and pose repeatability	17
7.3	Distance accuracy and repeatability 24 •	17
7.4	Position stabilization time	29
7.5	Position overshoot	30
7.6	Drift of pose characteristics	31
7.7	Exchangeability	34
8	Path characteristics	35
8.1	General	35
8.2	Path accuracy	36
8.3	Path repeatability	37
8.4	Path accuracy on reorientation	39
8.5	Cornering deviations	40
8.6	Path velocity characteristics	42
9	Minimum posing time	44
10	Static compliance	46
11	Application specific Performance criteria	46
11.1	Weaving deviations	46
12	Test report	48

Annex

A (normative) Parameters for comparison tests	49
B (informative) Guide for selection of tests for typical applications	54
C (informative) Example of a test report	56