DIN EN 1151-2:2006-11 (E)

Pumps - Rotodynamic pumps - Circulation pumps having a rated power input not exceeding 200 W for heating installations and domestic hot water installations - Part 2: Noise test code (vibro-acoustics) for measuring structure- and fluid borne noise

Contents

Page

Foreword 4

Introduction 5

1 Scope 6

2 Normative references 6

3 Terms and definitions 6

4 Test rig 7
4.1 General 7
4.2 Main components of test rig 7
4.3 Specification of test rig components 8
4.4 Assembly 11
4.5 Foundation 11
4.6 Qualifications 11
4.7 Instrumentation 11
4.7.1 Measurement of pressure fluctuations 11
4.7.2 Measurement of vibration 11
4.8 Calibration 12
4.8.1 Accelerometers 12
4.8.2 Pressure transducers 12
4.8.3 Calibration of accelerometers and pressure transducers 12
4.9 Propagation factors 12

5 Installation and operation of the tested pump 13
5.1 Installation of the pump 13
5.2 Operating parameters 14
5.3 Initial operation time 14

6 Factors influencing measurements 14
6.1 Electromagnetic surroundings 14
6.2 Earth loops 14
6.3 Vibration surroundings 14

7 Determination of fluid- and structure-borne powers 14
7.1 Frequency range 14
7.2 Measurement parameters 14
7.2.1 Pressure fluctuation measurement parameters 14
7.2.2 Vibration measurement parameters 15
7.3 Sense of power propagation 15
7.4 Fluid-borne power determination 15
7.4.1 General 15
7.4.2 Fluid-borne intensity 15
7.4.3 Fluid-borne power 16
7.5 Structure-borne power determination 16
7.5.1 General 16
7.5.2 Structure-borne intensity 16

7.5.3 Structure-borne power 17
7.6 Overall values of power 17
7.7 Coefficients of energy propagation and power levels 18
7.7.1 Coefficient of fluid-borne energy propagation 18
7.7.2 Coefficient of structure-borne energy propagation 18
7.7.3 Fluid-borne power level 18
7.7.4 Structure-borne power level 18

8 Information to be reported 19

Annex A (informative) Bending wavenumber and intensity dimensional constant 20

Bibliography 21