

# ISO 4156-1:2005-10 (E)

## Straight cylindrical involute splines - Metric module, side fit - Part 1: Generalities

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Symbols, subscripts and abbreviated terms .....</b>	<b>7</b>
<b>4.1</b>	<b>General symbols .....</b>	<b>7</b>
<b>4.2</b>	<b>Subscripts .....</b>	<b>9</b>
<b>4.3</b>	<b>Formulae for dimensions and tolerances for all fit classes .....</b>	<b>9</b>
<b>5</b>	<b>Concept of side fit splines .....</b>	<b>12</b>
<b>6</b>	<b>Effective fit concept .....</b>	<b>14</b>
<b>7</b>	<b>Basic rack profiles for spline .....</b>	<b>22</b>
<b>8</b>	<b>Spline fit classes .....</b>	<b>24</b>
<b>9</b>	<b>Space width and tooth thickness tolerances .....</b>	<b>26</b>
<b>9.1</b>	<b>Total tolerance <math>T +</math> .....</b>	<b>26</b>
<b>9.2</b>	<b>Deviation allowance, .....</b>	<b>27</b>
<b>9.3</b>	<b>Total pitch deviation, <math>F_p</math> .....</b>	<b>27</b>
<b>9.4</b>	<b>Total profile deviation, <math>F</math> .....</b>	<b>28</b>
<b>9.5</b>	<b>Total helix deviation, <math>F</math> .....</b>	<b>29</b>
<b>9.6</b>	<b>Machining tolerance, <math>T</math> .....</b>	<b>29</b>
<b>9.7</b>	<b>Effective clearance tolerance, <math>T_v</math> .....</b>	<b>30</b>
<b>9.8</b>	<b>Use of effective and actual dimensions for space width and tooth thickness .....</b>	<b>30</b>
<b>10</b>	<b>Minor and major diameters .....</b>	<b>31</b>
<b>10.1</b>	<b>Tolerances .....</b>	<b>31</b>
<b>10.2</b>	<b>Adjustment to minor diameters (Die), form diameters (<math>DF_e</math>) and major diameters (<math>De_e</math>) of external splines .....</b>	<b>32</b>
<b>11</b>	<b>Manufacturing and design considerations .....</b>	<b>32</b>
<b>11.1</b>	<b>Radii .....</b>	<b>32</b>
<b>11.2</b>	<b>Profile shifts .....</b>	<b>32</b>
<b>11.3</b>	<b>Eccentricity and misalignment .....</b>	<b>33</b>
<b>12</b>	<b>Spline data .....</b>	<b>34</b>
<b>12.1</b>	<b>Basic dimensions .....</b>	<b>34</b>
<b>12.2</b>	<b>Combination of types .....</b>	<b>34</b>
<b>12.3</b>	<b>Designation .....</b>	<b>34</b>
<b>12.4</b>	<b>Drawing data .....</b>	<b>35</b>
<b>Annex A (informative)</b>	<b>Drawing data example calculations .....</b>	<b>40</b>
<b>Bibliography .....</b>		<b>59</b>