

# ISO/OECD 789-10:2006-07 (E)

## Agricultural tractors - Test procedures - Part 10: Hydraulic power at tractor/implement interface

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Measurement units and tolerances .....</b>	<b>3</b>
<b>5</b>	<b>General requirements .....</b>	<b>3</b>
5.1	Specification .....	3
5.2	Running-in and preliminary adjustments .....	3
<b>6</b>	<b>Available hydraulic pressure test .....</b>	<b>4</b>
6.1	Steady state .....	4
6.1.1	Test conditions .....	4
6.1.2	Test procedures .....	5
6.1.2.1	Flow through single coupler pair -- Type 1 tests .....	5
6.1.2.2	Flow through single coupler pair -- Type 2 tests .....	5
6.1.2.3	Flow into sump return port with coupler -- Type 2 test .....	5
6.1.2.4	Flow into sump return port without coupler -- Type 2 test .....	5
6.2	Peak pressure .....	5
6.2.1	Test conditions .....	5
6.2.2	Test procedure -- Maximum flow selected -- Type 2 test .....	5
6.3	Test report -- Available hydraulic pressure .....	6
6.3.1	Type 1 tests .....	6
6.3.2	Type 2 tests .....	6
<b>7</b>	<b>Available hydraulic power .....</b>	<b>7</b>
7.1	Test conditions .....	7
7.2	Test procedures .....	7
7.2.1	Hydraulic power through single coupler pair -- Types 1 and 2 tests .....	7
7.2.2	Maximum available hydraulic power using two or more coupler pairs simultaneously -- Types 1 and 2 tests .....	8
7.3	Test report -- Available hydraulic power .....	8
7.3.1	Maximum available hydraulic power -- Type 1 tests .....	8
7.3.2	Maximum useable (continuous) available hydraulic power -- Type 2 tests .....	8
<b>Annex A (normative)</b>	<b>Specimen test report .....</b>	<b>10</b>
<b>Bibliography .....</b>		<b>14</b>