

ISO 10303-522:2006-07 (E)

Industrial automation systems and integration - Product data representation and exchange - Part 522: Application interpreted construct: Machining features

Contents		Page
1	Scope	1
2	Normative references	1
3	Terms, definitions and abbreviations	2
3.2	Other definitions	3
3.3	Abbreviations	3
4	EXPRESS short listing	3
4.1	Fundamental concepts and assumptions	5
4.2	AIC_machining_feature entity definitions	7
4.2.1	applied_area	7
4.2.2	boss	9
4.2.3	boss_top	14
4.2.4	chamfer	16
4.2.5	chamfer_offset	18
4.2.6	circular_pattern	20
4.2.7	circular_closed_profile	23
4.2.8	closed_path_profile	24
4.2.9	composite_hole	26
4.2.10	compound_feature	27
4.2.11	direction_shape_representation	29
4.2.12	edge_round	30
4.2.13	externally_defined_feature_definition	33
4.2.14	face_shape_representation	43
4.2.15	feature_component_definition	43
4.2.16	feature_component_relationship	44
4.2.17	feature_definition	45
4.2.18	feature_pattern	46
4.2.19	fillet	47
4.2.20	flat_face	50
4.2.21	gear	52
4.2.22	hole_bottom	58
4.2.23	instanced_feature	63
4.2.24	linear_profile	64
4.2.25	location_shape_representation	65
4.2.26	marking	66
4.2.27	modified_pattern	68
4.2.28	ngon_closed_profile	70
4.2.29	open_path_profile	72
4.2.30	outer_round	74
4.2.31	outside_profile	78
4.2.32	partial_circular_profile	84
4.2.33	path_feature_component	86
4.2.34	path_shape_representation	90
4.2.35	pattern_offset_membership	91
4.2.36	pattern_omit_membership	96
4.2.37	planar_shape_representation	100
4.2.38	pocket	100
4.2.39	pocket_bottom	107
4.2.40	profile_floor	110

4.2.41	protrusion	113
4.2.42	rectangular_closed_profile	114
4.2.43	rectangular_pattern	117
4.2.44	removal_volume	120
4.2.45	replicate_feature	121
4.2.46	revolved_profile	122
4.2.47	rib_top	126
4.2.48	rib_top_floor	127
4.2.49	round_hole	129
4.2.50	rounded_end	131
4.2.51	rounded_u_profile	133
4.2.52	shape_defining_relationship	135
4.2.53	shape_representation_with_parameters	136
4.2.54	spherical_cap	136
4.2.55	square_u_profile	138
4.2.56	step	142
4.2.57	slot	144
4.2.58	slot_end	148
4.2.59	taper	151
4.2.60	tee_profile	153
4.2.61	thread	158
4.2.62	thread_runout	163
4.2.63	transition_feature	165
4.2.64	turned_knurl	166
4.2.65	vee_profile	170
Annex A (normative) AIM short names		174
Annex B (normative) Information object registration		177
Annex C (informative) EXPRESS-G diagrams		178
Annex D (informative) Computer interpretable listings		189
Annex E (informative) Technical discussion		190
Bibliography		195
Index		196
Figures Figure 1 -- Pattern offset required instances		95
Figure 2 -- Pattern omit required instances		99
Figure C.1 -- EXPRESS-G diagram of the aic_machining_feature (1 of 10)		179
Figure C.2 -- EXPRESS-G diagram of the aic_machining_feature (2 of 10)		180
Figure C.3 -- EXPRESS-G diagram of the aic_machining_feature (3 of 10)		181
Figure C.4 -- EXPRESS-G diagram of the aic_machining_feature (4 of 10)		182
Figure C.5 -- EXPRESS-G diagram of the aic_machining_feature (5 of 10)		183
Figure C.6 -- EXPRESS-G diagram of the aic_machining_feature (6 of 10)		184
Figure C.7 -- EXPRESS-G diagram of the aic_machining_feature (7 of 10)		185
Figure C.8 -- EXPRESS-G diagram of the aic_machining_feature (8 of 10)		186
Figure C.9 -- EXPRESS-G diagram of the aic_machining_feature (9 of 10)		187
Figure C.10 -- EXPRESS-G diagram of the aic_machining_feature (10 of 10)		188
Tables Table A.1 -- AIM short names of entities		174