ISO 6336-3:2006-09 (E)

Calculation of load capacity of spur and helical gears - Part 3: Calculation of tooth bending strength

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Terms, definitions, symbols and abbreviated terms 1

4 Tooth breakage and safety factors 2

5 Basic formulae 2
5.1 Safety factor for bending strength (safety against tooth breakage), SF 2
5.2 Tooth root stress, F 2
5.3 Permissible bending stress, FP 4

6 Form factor, YF 8
6.1 General 8
6.2 Calculation of the form factor, YF: Method B 9
6.3 Derivations of determinant normal tooth load for spur gears 13

7 Stress correction factor, YS 14
7.1 Basic uses 14
7.2 Stress correction factor, YS: Method B 14
7.3 Stress correction factor for gears with notches in fillets 15
7.4 Stress correction factor, YST, relevant to the dimensions of the standard reference test gears 15

8 Helix angle factor, Y 15
8.1 Graphical value 16
8.2 Determination by calculation 16

9 Rim thickness factor, YB 16
9.1 Graphical values 16
9.2 Determination by calculation 17

10 Deep tooth factor, YDT 18
10.1 Graphical values 18
10.2 Determination by calculation 18

11 Reference stress for bending 19
11.1 Reference stress for Method A 19
11.2 Reference stress, with values F lim and FE for Method B 19

12 Life factor, YNT 19
12.1 Life factor, YNT: Method A 19
12.2 Life factor, YNT: Method B 19

13 Sensitivity factor, YT, and relative notch sensitivity factor, Y rel T 21
13.1 Basic uses 21

13.2 Determination of the sensitivity factors 21
13.3 Relative notch sensitivity factor, Y rel T: Method B 22

14 Surface factors, YR, YRT, and relative surface factor, YR rel T 27
14.1 Influence of surface condition 27
14.2 Determination of surface factors and relative surface factors 28
14.3 Relative surface factor, YR rel T: Method B 28

15 Size factor, YX 30
15.1 Size factor, YX: Method A 30
15.2 Size factor, YX: Method B 30

Annex A (normative) Permissible bending stress, FP, obtained from notched, flat or plain polished test pieces 33

Annex B (informative) Guide values for mean stress influence factor, YM 40

Bibliography 42